

BAP-SV1610S: Stop valve DN10



Commercial information

Henco stopbolkraan in messing. Met persaansluiting

Basic unit dimensions

Height	23 mm
Length	75 mm
Width	23 mm
Net weight	0.110 kg

Certificates

Applications

Potable water, Heating, Sanitary

Solutions

Building installations, Industry, Utility

Technical characteristics

Surface protection ball	None	Diameter bolt hole	16
Material secondary spindle seal	Ethylene-propylene diene monomer rubber (EPDM)	Outer pipe diameter connection 1	16 Millimetre
Nominal diameter connection 1	DN 8	Outer pipe diameter connection 2	10 Millimetre
Connection 1	Press sleeve	Medium temperature (continuous)	-10 70 Degrees celsius
With coupling connection 1	✓	Wrench width	0 Millimetre
Contour code connection 1	TH/BE	Wrench width union nut	0 Millimetre
Nominal diameter connection 2	DN 10		
Connection 2	External thread conical BSPT-R (ISO 7-1 / EN 10226-1)		
With coupling connection 2	✓		
Sealing	Ethylene-propylene diene monomer rubber (EPDM)		
With drain valve	✗		
With drain possibility (connection)	✓		
With filter	✗		
With thermometer	✗		
Model	Straight		
With insulation shell	✗		
FM quality mark	✗		
UL quality mark	✗		
ULC quality mark	✗		
LPCB quality mark	✗		
Fire-safe	✗		
Medically clean	✗		
Grease-free	✗		
Full bore	✗		
KIWA certified	✗		