


## VSK-1616: Extension or body for manifold, 2 SK connections Ø16



### Commercial information

Synthetic manifold or extension with SK connectors Ø16

#### Basic unit dimensions

Height	30 mm
Length	124 mm
Width	66 mm
Net weight	0.102 kg

#### Certificates

QB (CSTBat), ETA, KIWA, ÖVGW Wasser, SINTEF, SITAC, KOMO, STF, GOST-R, TSU, EMI

#### Applications

Potable water, Heating, Cooling, Sanitary

#### Solutions

Building installations, Industry, Utility

## Technical characteristics

Suitable for tap water	✓	Outer pipe diameter connection 1	16 Millimetre
Suitable for central heating water	✓	Outer pipe diameter connection 2	0 Millimetre
Suitable for cooling water	✓	Number of branches	2
Suitable for compressed air	✗	Number of branching directions	1
Suitable for glycol	✓	Distance between offset	50 Millimetre
Mounting method	Surface mounting	Max. medium temperature (continuous)	70 Degrees celsius
Model	Distributor/collector	Width	66 Millimetre
Material	Plastic	Height	30 Millimetre
Material quality	Polyvinylidene fluoride (PVDF)	Length distributor	124 Millimetre
Surface protection	Untreated		
Shape	Throughflow with straight branches		
Connection 1	Insert (push-fitting)		
Nominal diameter connection 2	3/4 inch (20)		
Connection 2	External thread cylindrical BSPP-G (ISO 228-1)		
Nominal diameter branches	DN 15		
Connection branches	Other		
Deviant distance between branches	✗		
With filling/drain tap	✗		
System specific	✓		
With shut-off valve	✗		
With de-aeration	✗		
With wall-mounting bracket	✗		
With mounting material	✗		
With legs	✗		
With insulation	✗		
KOMO certified	✓		
Type approval according to BBR/EKS	✗		