

## Data Sheet | Item Number: 770-201

Lockout cap; 12-pole, separable; for sockets; Plastic; black

<https://www.wago.com/770-201>



Color: ■ black

### Cover WINSTA® MIDI 12-pole

Put your trust in reliable accuracy for the electrical installation at your construction site: The cover from the WINSTA® MIDI product line. An extensive range of accessories rounds out the WINSTA® product line from WAGO. The WINSTA® MIDI product line guarantees maximum flexibility for the electrical installation. Through its Push-in CAGE CLAMP® spring pressure connection technology, it guarantees time-saving, error-free installation and offers flexibility and customization for meeting all installation requirements.

Lower costs through fast commissioning and elimination of service expenses – solutions from WINSTA® MIDI

The WINSTA® Pluggable Connection System allows pluggable electrical installation. This saves time, lowers costs, and reduces the need for servicing. Now you can also reduce installation costs without compromising safety and quality: with protection against mismatching eliminates the need for servicing and prevents unnecessary downtime.

- for automation controllers
- convenient installation and commissioning

### Notes

General safety information

#### **NOTICE: Observe installation and safety instructions!**

- Nur von Elektrofachkraft oder einer für die Tätigkeit elektrisch unterwiesenen Person (EUP nach DIN VDE 0105-100) anzuwenden!
- Nicht unter Spannung/Last installieren!
- Nur für bestimmungsgemäßen Gebrauch einsetzen!
- Nationale Vorschriften/Normen/Richtlinien beachten!
- Technische Daten der Produkte beachten!
- Auf die richtige Polbelegung achten!
- Keine beschädigten/verschmutzten Komponenten verwenden!
- Leiterarten, -querschnitte, Abisolierlängen und Leitungsdurchmesser beachten!
- Leiter bis zum Anschlag einführen!
- Nur mit Verriegelungsklinke und Zugentlastung verwenden!
- Originalzubehör verwenden!

**To be sold only with installation instructions!**

## Connection Data

### Connection 1

Pole number	12
-------------	----

## Mechanical data

Suitable	for socket; separable
----------	-----------------------

## Material data

Note (material data)	<a href="#">Information on material specifications can be found here</a>
Color	black
Insulation material (main housing)	Polyamide (PA66)
Flammability class per UL94	V0
Fire load	0.013 MJ
Weight	0.4 g

## Environmental requirements

Processing temperature	-5 ... +40 °C
Continuous operating temperature	-35 ... +85 °C
Note on continuous operating temperature	Insulating parts for temperatures ≤ 105 °C

## Commercial data

Product Group	20 (Winsta)
PU (SPU)	100 pcs
Packaging type	Bag
Country of origin	DE
GTIN	4017332755252
Customs tariff number	39269097900

## Product Classification

UNSPSC	39121421
eCl@ss 10.0	27-44-06-92
eCl@ss 9.0	27-44-06-92
ETIM 9.0	EC002863
ETIM 10.0	EC002863
ECCN	NO US CLASSIFICATION

## Environmental Product Compliance

RoHS Compliance Status	Compliant, No Exemption
------------------------	-------------------------

Approvals / Certificates

General approvals



Approval	Standard	Certificate Name
VDE VDE Prüf- und Zertifizierungsinstitut	EN 61535	40029808

Downloads

Environmental Product Compliance

Compliance Search

Environmental Product Compliance 770-201	↓
--	---

Documentation

Bid Text

770-201	19.02.2019	xml 2.57 KB	↓
770-201	13.01.2015	doc 21.50 KB	↓

CAD/CAE-Data

CAD data

2D/3D Models 770-201	↓
----------------------	---

CAE data

WSCAD Universe 770-201	↓
ZUKEN Portal 770-201	↓