

## START Downlight Eco 95mm Round Recessed

START Eco Downlight 95 640lm 840  
0053914



### PRODUCT OVERVIEW


Product name	START Eco Downlight 95 640lm 840
Technology	LED
Cap/Base	N/A
Housing	PC Polycarbonate
Mount	Ceiling recessed mounting
Warranty	3 years
Fixture luminous flux (lm)	640
Luminaire efficacy (lm/W)	80
Colour temperature (K)	4000
Light colour	Neutral White
CRI (Ra)	80
Colour Variation Initial (SDCM)	SDCM6
Glare control	< 28
Photobiological Risk Group	RG0
Total power consumption (W)	8
Electrical protection	Class II
LED Flickering Rate	Medium (21% - 40%)
Housing colour	RAL 9003 - Signal white
IP rating	IP20
IK rating	IK02
Product EAN number	5410288539140

### PHOTOMETRY

## START Downlight Eco 95mm Round Recessed

*START Eco Downlight 95 640lm 840*  
0053914

0.5	1.56	607 E(CO)	87.2°	642 87
1.0	3.12	607 E(CO)	87.2°	321 71
1.5	4.67	607 E(CO)	87.2°	94 7
2.0	6.23	607 E(CO)	87.2°	69 4
2.5	7.79	607 E(CO)	87.2°	34 3
3.0	9.35	607 E(CO)	87.2°	22 2
Distance [m]	Cone diameter [m]			Illuminance [lx]
— C0 - C180 (Half beam angle: 114.6°)				



### TECHNICAL DRAWINGS

