

3 Phase Track

Spot COB | 24° | 36°

169-280

169-281

169-285

169-286

169-350

169-351

169-355

169-356



TRONIX
guided by light



Technical data

3 Phase Track | Spot COB

Input voltage	AC 220-240V
Power	10, 20 or 32 Watt
Power factor	>0,92 or >0,97
LED type	Citizen COB
Color LED	Warm white or Natural white
Beam	24° or 36°
CRI	>90
IP rate	IP20
Connection type	3-phase adaptor
Housing color	White or Black



Technical data

Technical data per product

	169-280	169-281	169-285	169-286
Power	10 Watt	10 Watt	20 Watt	20 Watt
Dimmable	No	No	Yes, triac	Yes, triac
Color temp.	3000K	3000K	3000K	3000K
Light output	800 Lm	800 Lm	1684 Lm	1684 Lm
Beam	24°	24°	24°	24°
Diameter	60 mm	60 mm	70 mm	70 mm
Length	165 mm	165 mm	210 mm	210 mm
Housing color	White	Black	White	Black

Technical data per product

	169-350	169-351	169-355	169-356
Power	32 Watt	32 Watt	32 Watt	32 Watt
Dimmable	Yes, triac	Yes, triac	No	No
Color temp.	3000K	3000K	4000K	4000K
Light output	2676 Lm	2676 Lm	2900 Lm	2900 Lm
Beam	36°	36°	36°	36°
Diameter	85 mm	85 mm	85 mm	85 mm
Length	235 mm	235 mm	235 mm	235 mm
Housing color	Black	White	Black	White

Accessories

Reflector

	Beam	To use with
169-357	15°	169-350 / 169-351 / 169-355 / 169-356
169-358	24°	169-350 / 169-351 / 169-355 / 169-356
169-359	60°	169-350 / 169-351 / 169-355 / 169-356

