



Color: ■ black

Mounting accessories *WINSTA®* MINI

The mounting accessories from the *WINSTA®* MINI product line guarantees you the maximum flexibility in electrical installation. A comprehensive range of accessories rounds out the *WINSTA®* product line from WAGO. Where space is tight, our smallest pluggable connection system, *WINSTA®* MINI, consistently displays its advantageous properties. It is very compact, and, thanks to Push-in CAGE CLAMP® spring pressure connection technology, it additionally can be installed quickly, since the connection is low-maintenance and requires no screw connections.

WINSTA® MINI solutions for your electrical installation – protected against mismatching and maintenance-free

The *WINSTA®* Pluggable Connection System allows pluggable electrical installation. This saves time, lowers costs, and reduces the need for servicing. Enjoy the benefits of the pluggable version of our maintenance-free spring pressure connection technology too! Plan your installation with with protection against mismatching from WAGO.

- consistent IP40 protection
- quick replacement of defective units during ongoing operation

Notes	
General safety information	NOTICE: Observe installation and safety instructions! • Nur von Elektrofachkraft oder einer für die Tätigkeit elektrisch unterwiesenen Person (EUP nach DIN VDE 0105-100) anzuwenden! • Nicht unter Spannung/Last installieren! • Nur für bestimmungsgemäßen Gebrauch einsetzen! • Nationale Vorschriften/Normen/Richtlinien beachten! • Technische Daten der Produkte beachten! • Auf die richtige Polbelegung achten! • Keine beschädigten/verschmutzten Komponenten verwenden! • Leiterarten, -querschnitte, Abisolierlängen und Leitungsdurchmesser beachten! • Leiter bis zum Anschlag einführen! • Nur mit Verriegelungsklinke und Zugentlastung verwenden! • Originalzubehör verwenden! To be sold only with installation instructions!

Physical data

Width	60.2 mm / 2.37 inches
Height	30.6 mm / 1.205 inches
Depth	77.8 mm / 3.063 inches

Mechanical data

Suitable	for flying leads; 2- to 5-pole
----------	--------------------------------

Material data

Note (material data)	Information on material specifications can be found here
Color	black
Insulation material (main housing)	Polyamide (PA66)
Flammability class per UL94	V0
Fire load	0.149 MJ
Weight	5 g

Environmental requirements

Processing temperature	-5 ... +40 °C
Continuous operating temperature	-35 ... +85 °C
Note on continuous operating temperature	Insulating parts for temperatures ≤ 105 °C

Commercial data

Product Group	20 (Winsta)
PU (SPU)	100 pcs
Packaging type	Bag
Country of origin	DE
GTIN	4050821255093
Customs tariff number	39269097900

Product Classification

UNSPSC	39121402
eCl@ss 10.0	27-44-06-92
eCl@ss 9.0	27-44-06-92
ETIM 9.0	EC002863
ETIM 10.0	EC002863
ECCN	NO US CLASSIFICATION

Environmental Product Compliance

RoHS Compliance Status	Compliant, No Exemption
------------------------	-------------------------



Downloads			
Environmental Product Compliance			
Compliance Search			
Environmental Product Compliance 890-310			↓

Documentation			
Bid Text			
890-310	19.02.2019	xml 2.61 KB	↓
890-310	20.11.2014	doc 21.50 KB	↓

CAD/CAE-Data	
CAD data	CAE data
2D/3D Models 890-310	WSCAD Universe 890-310
↓	↓
	ZUKEN Portal 890-310
	↓