

Product data sheet

Item No. 96.141.1053.0

Female connector RST20i4C B1 M01 GL

Device connectors, standard M25, RST20i4, 4 pole, female, crimp connection, 250/400V, 20A, color of coding: light gray, color of nut: light gray



Item No.	96.141.1053.0
EAN	4015573939455
Order Unit	100 Piece(s)

Certificates / Approvals



Technical data

General

Rated current	20 A
Rated voltage	400 V
Pollution degree	3
Mechanical coding	Yes
Rated impulse voltage	4 kV
Interlockable	Yes
Color of coding/ contact carrier	Light grey
Marking of poles	

Connection Data

Connection cross section solid	4 mm ²
Connection cross section stranded	4 mm ²
Terminations per pole	1

Model

Model	female
Number of poles	4
Connection type	Crimp



Connecting thread metric	M25
Angle of plug	Straight
Degree of protection (IP)	IP66/IP68
Built-in component	Snap-in/screw-in

Material

Housing material	Polyamide
Halogen free	Yes
Contact material	CuZn
Insulation components continuous temperature	100 °C
Surface finish	Silver-plated

Dimensions

Length	44 mm
Width	35 mm
Height	35 mm

Technical drawing

**Bestellinfo
order info**

Bitte separat bestellen:
Buchsenkontakt
02.125.55/56/57/58/21.8

Female contact
02.125.55/56/57/58/21.8
must be ordered separately

**Gehäuseausschnitt
out cut**

1 max. = 8mm
wahlweise 11,7^{+0,2}
optional 11,7^{+0,2}

Verpackungseinheit: je 100 Stück
packaging unit: per 100

Teile-Nr./ part-nr.	Farbe/ color:	Einzel-Tl.-Nr./ single-part-no.:	Type
96.141.1053.1	schwarz, öhnl. RAL 9005/ black, similar to RAL 90051	RST2014C BI M01V SW
96.141.1053.0	lichtgrau, öhnl. RAL 7035/ lightgrey, similar to RAL 70350	RST2014C BI M01V GL

BUCHSENTEIL

96.141.1053.0 01K