


START Surface Wall Cube IP54 2x140lm 2CCT White
0047137



Features

- Exterior adjustable surface wall up and down light luminaire, RAL9016 - Traffic White colour, 280lm, 5.8W, 48lm/W, 3000/4000K switchable CCT, adjustable beam angle (0 - 94°), 104.000 hrs L70:B50 lifespan, CRI 80, SDCM<3, IP54, IK05, 1000 hrs salt spray test, -20 - +45°C operating temperature range, 108x108x108mm, Class I


Product Overview

Product name	START Surface Wall Cube IP54 2x140lm 2CCT White
Technology	LED
Cap/Base	N/A
Housing	Aluminium
Mount	Wall surface mounted
General application	Residential & Consumer
ETIM Class	EC002892
E-number FI	4579606
Fixture luminous flux (lm)	280
Luminaire efficacy (lm/W)	48
Light colour	Warm White or Neutral White
CRI (Ra)	80
Colour Variation Initial (SDCM)	3
Photobiological Risk Group	RG1
Total power consumption (W)	5.8
Electrical protection	Class I
Control gear type	LED driver constant current
Dimmable	No
Housing colour	White
IP rating	IP54


START Surface Wall Cube IP54 2x140lm 2CCT White
0047137

IK rating	IK05
Product EAN number	5410288471372
Warranty	5 years
Dimming method	N/A

Photometry



Technical drawings



START Surface Wall Cube IP54 2x140lm 2CCT White 0047137

Data table

GENERAL DATA

Product name	START Surface Wall Cube IP54 2x140lm 2CCT White
Technology	LED
Cap/Base	N/A
Housing	Aluminium
Mount	Wall surface mounted
General application	Residential & Consumer
Operating temperature range (°C)	-20°C...+45°C
ETIM Class	EC002892
E-number FI	4579606
Warranty	5 years

OPTICAL DATA

Fixture luminous flux (lm)	280
Luminaire efficacy (lm/W)	48
Light colour	Warm White or Neutral White
CRI (Ra)	80
Colour Variation Initial (SDCM)	3
Distribution type	Adjustable
Photobiological Risk Group	RG1

ELECTRICAL DATA

Total power consumption (W)	5.8
Primary Supply/Product voltage - min (V)	220
Primary Supply/Product voltage - max (V)	240
Lamp power factor	0.66
THD (at 230 V, 50 Hz, full load, at 100% dimming level) ≤ xx.x %	46
Electrical protection	Class I
Control gear required	No

START Surface Wall Cube IP54 2x140lm 2CCT White 0047137

Control gear type	LED driver constant current
Dimmable	No
Dimming method	N/A
Inrush Current (A)	10
Energy Efficiency Class (A->G) of contained light source	F
Nominal Frequency (Hz)	50/60Hz
Max. products per 10A C Breaker	70
Max. products per 13A C Breaker	86
Max. products per 16A C Breaker	100
Max. products per 20A C Breaker	100
Max. products per 10A B Breaker	56
Max. products per 13A B Breaker	68
Max. products per 16A B Breaker	82
Max. products per 20A B Breaker	96
Connectable conductor cross section - Max (mm ²)	1.5

LIFETIME DATA

Lifespan L70 B50	104000
Lifespan L70 B20	101000
Lifespan L70 B10	98700
Lifespan L80 B50	68000
Lifespan L80 B20	67000
Lifespan L80 B10	67000
Lifespan L90 B50	36000
Lifespan L90 B20	35000
Lifespan L90 B10	35000

PHYSICAL DATA

Housing colour	White
IP rating	IP54
IK rating	IK05
Diffuser finish	Transparent



START Surface Wall Cube IP54 2x140lm 2CCT White
0047137

Diffuser material	Glass
Nominal Product Length (mm)	108
Nominal Product Width (mm)	108
Nominal Product Height (mm)	109
Weight (kg)	0.785

PACKAGING

Product EAN number	5410288471372
Packaging single length / height (cm)	14.5
Packaging single width (cm)	14.5
Packaging single depth (cm)	14.5
DUN14 (inner)	15410288471379
Units per outer package	8
Packaging outer length / height (cm)	60.0
Packaging outer width (cm)	31.0
Packaging outer depth (cm)	16.5

SAFETY DATA

Glow Wire Test (°C)	650
Optimal operating condition (°C)	-20-45
Special purpose lamp	No
Dry applications use only	No
Suitable for household illumination	No