



Color: ■ white

Dimensions in mm  
Plate thickness: 0.5 ... 2 mm Cutout tolerance: + 0.1 mm Please note!

#### Cover WINSTA® MINI 3-pole

Put your trust in reliable safety for the electrical installation in your project: The cover from the WINSTA® MINI product line. An extensive range of accessories complements the WINSTA® product line from WAGO. Due to its particularly compact dimensions, our WINSTA® MINI Pluggable Connection System with Push-in CAGE CLAMP® spring pressure connection technology is specifically suitable in very tight spaces, i.e., for connections when very little room is available.

Push-in CAGE CLAMP® spring pressure connection technology – pluggable installation instead of laborious screw connections!

WINSTA® is the pluggable connection system that is ideally tailored to the strict requirements of electrical installation. It ensures error-free installation of cables and components, quickly and reliably. Now you can also cut installation expenses without compromising quality and safety: with protection against mismatching reduces the need for servicing and prevents unnecessary downtime.

- consistent IP40 protection
- quick replacement of defective units during ongoing operation

#### Notes

General safety information

#### NOTICE: Observe installation and safety instructions!

- Nur von Elektrofachkraft oder einer für die Tätigkeit elektrisch unterwiesenen Person (EUP nach DIN VDE 0105-100) anzuwenden!
- Nicht unter Spannung/Last installieren!
- Nur für bestimmungsgemäßen Gebrauch einsetzen!
- Nationale Vorschriften/Normen/Richtlinien beachten!
- Technische Daten der Produkte beachten!
- Auf die richtige Polbelegung achten!
- Keine beschädigten/verschmutzten Komponenten verwenden!
- Leiterarten, -querschnitte, Abisolierlängen und Leitungsdurchmesser beachten!
- Leiter bis zum Anschlag einführen!
- Nur mit Verriegelungsklinke und Zugentlastung verwenden!
- Originalzubehör verwenden!

#### To be sold only with installation instructions!

The snap-in connectors must be relieved of tensile and transverse forces. A surface finish can influence the edge radius of the cutouts. This may affect the snap-in socket fit, so ensure an adequate fit before use. In addition, the punched edge should be on the inside for punched cutouts. The wings of the snap-in connectors must not be mechanically stressed for a long period before use (e.g., due to a pre-locking position).

Note

## Connection Data

### Connection 1

Pole number	3
-------------	---

## Physical data

Width	21.6 mm / 0.85 inches
Height	16 mm / 0.63 inches
Depth	10.1 mm / 0.398 inches

## Mechanical data

Mounting type	Snap-in flange
Suitable	for cutout

## Material data

Note (material data)	<a href="#">Information on material specifications can be found here</a>
Color	white
Insulation material (main housing)	Polyamide (PA66)
Flammability class per UL94	V0
Fire load	0.041 MJ
Weight	1.4 g

## Environmental requirements

Processing temperature	-5 ... +40 °C
Continuous operating temperature	-35 ... +85 °C
Note on continuous operating temperature	Insulating parts for temperatures ≤ 105 °C

## Commercial data

Product Group	20 (Winsta)
PU (SPU)	100 pcs
Packaging type	Box
Country of origin	DE
GTIN	4045454526528
Customs tariff number	39269097900

## Product Classification

UNSPSC	39121702
eCl@ss 10.0	27-44-06-92
eCl@ss 9.0	27-44-06-92
ETIM 9.0	EC002863
ETIM 10.0	EC002863
ECCN	NO US CLASSIFICATION

Environmental Product Compliance	
RoHS Compliance Status	Compliant, No Exemption

### Downloads

#### Environmental Product Compliance

Compliance Search	
Environmental Product Compliance 890-693	<a href="#">↓</a>

### Documentation

Bid Text			
890-693	19.02.2019	xml 2.56 KB	<a href="#">↓</a>
890-693	26.11.2014	doc 22.50 KB	<a href="#">↓</a>

### CAD/CAE-Data

CAD data	
2D/3D Models 890-693	<a href="#">↓</a>

CAE data	
WSCAD Universe 890-693	<a href="#">↓</a>
ZUKEN Portal 890-693	<a href="#">↓</a>

Subject to changes. Please also observe the further product documentation!

Current addresses can be found at: [www.wago.com](https://www.wago.com)