Data Sheet | Item Number: 772-260

Mounting plate; for power supply and tap-off modules; Plastic; black

https://www.wago.com/772-260



Color: ■ black

Mounting accessories *WINSTA*® IDC

Choose realiable safety for the electrical installation for the implementation of your project: The mounting accessories from the *WINSTA*® IDC product line. You can rely on the level of quality of WINSTA® components from WAGO for your electrical installation accessories too.

WINSTA® IDC solutions for your electrical installation – protected against mismating and maintenance-free

WINSTA® is the pluggable connection system that is perfectly tailored to the strict requirements of electrical installation. It allows error-free installation of cables and components, quickly and reliably. Choose durability and quality – with protection against mismating from WAGO makes the electrical installation of electrical components noticeably easier.

- products perfectly tailored to your requirements guarantee safe use
- quick replacement of defective units during ongoing operation

Notes

General safety information	**NOTICE: Observe installation and safety instructions!** • Nur von Elektrofachkraft oder einer für die Tätigkeit elektrisch unterwiesenen Person (EUP nach DIN VDE 0105-100) anzuwenden! • Nicht unter Spannung/Last installieren! • Nur für bestimmungsgemäßen Gebrauch einsetzen! • Nationale Vorschriften/Normen/Richtlinien beachten! • Technische Daten der Produkte beachten! • Auf die richtige Polbelegung achten! • Keine beschädigten/verschmutzten Komponenten verwenden! • Leiterarten, -querschnitte, Abisolierlängen und Leitungsdurchmesser beachten! • Leiter bis zum Anschlag einführen! • Nur mit Verriegelungsklinke und Zugentlastung verwenden! • Originalzubehör verwenden! **To be sold only with installation instructions!**

Mechanical data

Mounting type	Screw mount
Suitable	for supply and tap-off modules

Material data

Note (material data)	Information on material specifications can be found here
Color	black
Insulation material (main housing)	Polyamide (PA66)
Flammability class per UL94	V0
Fire load	0.346 MJ
Weight	11.6 g

Environmental requirements

Processing temperature	-5 … +40 °C
Continuous operating temperature	-35 … +85 °C
Note on continuous operating temperature	Insulating parts for temperatures ≤ 105 °C

Commercial data

Product Group	20 (Winsta)
PU (SPU)	10 pcs
Packaging type	Box
Country of origin	DE
GTIN	4045454543983
Customs tariff number	39269097900

Product Classification

UNSPSC	39121311
eCl@ss 10.0	27-44-06-92
eCl@ss 9.0	27-44-06-92
ETIM 9.0	EC002863
ETIM 10.0	EC002863
ECCN	NO US CLASSIFICATION

Environmental Product Compliance

RoHS Compliance Status	Compliant,No Exemption

Downloads

Environmental Product Compliance

Compliance Search

Environmental Product Compliance 772-260

Documentation

Bid Text

772-260	19.02.2019	xml 2.57 KB	
772-260	09.01.2015	doc 22.50 KB	

CAD/CAE-Data

CAD data

2D/3D Models 772-260

CAE data

WSCAD Universe
772-260

ZUKEN Portal 772-260