

Data Sheet | Item Number: 770-101

Locking lever; for flying leads; for manual operation; black

<https://www.wago.com/770-101>



Color: ■ black

Locking system WINSTA® MIDI

Implement your installation project with ease: The locking system from the WINSTA® MIDI product line is the solution for error-free electrical installation. A comprehensive range of accessories rounds out the WINSTA® product line from WAGO. The WINSTA® MIDI Pluggable Connection System with Push-in CAGE CLAMP® spring pressure connection technology facilitates exemplary electrification. Due to the built-in test slot, it is possible to check connections even when they are plugged in. This saves time, labor, and money.

WINSTA® MIDI solutions for your electrical installation – protected against mismatching and maintenance-free

The WINSTA® Pluggable Connection System is ideally tailored to the very strict requirements of building installation. It makes electrical installation pluggable, and consequently more efficient, even more reliable, and error-free. Using this pre-assembled system decreases time spent on assembly and installation errors at the construction site. Choose durability and quality – with protection against mismatching from WAGO makes the electrical installation of electrical components visibly easier.

- pre-assembled versions
- fast, secure installation

Notes

General safety information

NOTICE: Observe installation and safety instructions!

- Nur von Elektrofachkraft oder einer für die Tätigkeit elektrisch unterwiesenen Person (EUP nach DIN VDE 0105-100) anzuwenden!
- Nicht unter Spannung/Last installieren!
- Nur für bestimmungsgemäßen Gebrauch einsetzen!
- Nationale Vorschriften/Normen/Richtlinien beachten!
- Technische Daten der Produkte beachten!
- Auf die richtige Polbelegung achten!
- Keine beschädigten/verschmutzten Komponenten verwenden!
- Leiterarten, -querschnitte, Abisolierlängen und Leitungsdurchmesser beachten!
- Leiter bis zum Anschlag einführen!
- Nur mit Verriegelungsklinke und Zugentlastung verwenden!
- Originalzubehör verwenden!

To be sold only with installation instructions!

Connection Data

Connection 1

Actuation type	Finger-operated lever
----------------	-----------------------

Mechanical data

Suitable	for flying leads; manually operated
----------	-------------------------------------

Material data

Note (material data)	Information on material specifications can be found here
Color	black
Insulation material (main housing)	Polyamide (PA66)
Flammability class per UL94	V0
Fire load	0.022 MJ
Weight	0.6 g

Environmental requirements

Processing temperature	-5 ... +40 °C
Continuous operating temperature	-35 ... +85 °C
Note on continuous operating temperature	Insulating parts for temperatures ≤ 105 °C

Commercial data

Product Group	20 (Winsta)
PU (SPU)	100 (25) pcs
Packaging type	Box
Country of origin	DE
GTIN	4017332660907
Customs tariff number	85389099990

Product Classification

UNSPSC	39121702
eCl@ss 10.0	27-44-06-92
eCl@ss 9.0	27-44-06-92
ETIM 9.0	EC002863
ETIM 10.0	EC002863
ECCN	NO US CLASSIFICATION

Environmental Product Compliance

RoHS Compliance Status	Compliant, No Exemption
------------------------	-------------------------

Approvals / Certificates

General approvals



Approval	Standard	Certificate Name
VDE VDE Prüf- und Zertifizierungsinstitut	EN 61535	40029808

Downloads

Environmental Product Compliance

Compliance Search

Environmental Product Compliance 770-101



Documentation

Bid Text

Item	Date	File Type	Size	Action
770-101	19.02.2019	xml	2.62 KB	
770-101	11.03.2015	doc	21.50 KB	

CAD/CAE-Data

CAD data

2D/3D Models 770-101



CAE data

WSCAD Universe 770-101



ZUKEN Portal 770-101



Installation Notes

Locking system



Locking lever, manually operated:

- Push on locking lever
- Pull the connectors apart

Subject to changes. Please also observe the further product documentation!

Current addresses can be found at: www.wago.com