

Data Sheet | Item Number: 897-120

Flat cable end cover; for flat cable 2 x 1.5 mm²; Plastic; transparent

<https://www.wago.com/897-120>



Color: transparent

Cover WINSTA® IDC

Implement the electrical installation with ease: The cover from the WINSTA® IDC product line is the product of your choice for error-free electrical installation. You can rely on the level of quality of WINSTA® components from WAGO for your electrical installation accessories too.

WINSTA® IDC solutions for your electrical installation – protected against mismatching and maintenance-free

The WINSTA® Pluggable Connection System allows pluggable electrical installation. This significantly reduces the need for servicing and lowers costs. Enjoy the benefits of the pluggable version of our maintenance-free spring pressure connection technology tool! Plan your installation with with protection against mismatching from WAGO.

- products perfectly tailored to your requirements guarantee safe use
- rapid, structured electrical installation

Notes

General safety information

NOTICE: Observe installation and safety instructions!

- Nur von Elektrofachkraft oder einer für die Tätigkeit elektrisch unterwiesenen Person (EUP nach DIN VDE 0105-100) anzuwenden!
- Nicht unter Spannung/Last installieren!
- Nur für bestimmungsgemäßen Gebrauch einsetzen!
- Nationale Vorschriften/Normen/Richtlinien beachten!
- Technische Daten der Produkte beachten!
- Auf die richtige Polbelegung achten!
- Keine beschädigten/verschmutzten Komponenten verwenden!
- Leiterarten, -querschnitte, Abisolierlängen und Leitungsdurchmesser beachten!
- Leiter bis zum Anschlag einführen!
- Nur mit Verriegelungsklinke und Zugentlastung verwenden!
- Originalzubehör verwenden!

To be sold only with installation instructions!

Mechanical data

Variable coding	No
Suitable	for flat cable 2 x 1.5 mm ²

Material data

Note (material data)	Information on material specifications can be found here
Color	transparent
Insulation material (main housing)	Polyamide (PA66)
Flammability class per UL94	V0
Fire load	0.072 MJ
Weight	2.8 g

Environmental requirements

Processing temperature	-5 ... +40 °C
Continuous operating temperature	-35 ... +85 °C
Note on continuous operating temperature	Insulating parts for temperatures ≤ 105 °C

Commercial data

Product Group	20 (Winsta)
PU (SPU)	10 pcs
Packaging type	Box
Country of origin	CH
GTIN	4045454205119
Customs tariff number	85472000900

Product Classification

UNSPSC	39121409
eCl@ss 10.0	27-44-06-92
eCl@ss 9.0	27-44-06-92
ETIM 9.0	EC002863
ETIM 10.0	EC002863
ECCN	NO US CLASSIFICATION

Environmental Product Compliance

RoHS Compliance Status	Compliant, No Exemption
------------------------	-------------------------

Downloads

Environmental Product Compliance

Compliance Search

Environmental Product
Compliance 897-120



Documentation

Bid Text

897-120	19.02.2019	xml 2.59 KB	
897-120	09.01.2015	doc 22.50 KB	

CAD/CAE-Data

CAE data

WSCAD Universe 897-120	
---------------------------	---