

**Data Sheet | Item Number: 895-1605**  
Filler plug; M25 x 1.5 with O-ring; Plastic; black

<https://www.wago.com/895-1605>



Color: ■ black

#### Cover WINSTA® IDC

The cover from the WINSTA® IDC product line is the sophisticated solution for trouble-free electrical installation. You can rely on the quality of WINSTA® components from WAGO for your electrical installation accessories too.

WINSTA® IDC solutions for your electrical installation – protected against mismatching and maintenance-free

The WINSTA® Pluggable Connection System is ideally tailored to the very strict requirements of building installation. It makes electrical installation pluggable, and consequently more efficient, more reliable, and error-free. Using this pre-assembled system decreases assembly times and installation errors at the construction site. Choose quality and durability – with protection against mismatching from WAGO makes the installation of electrical components visibly easier.

- saves time, since no wiring is required at the construction site
- convenient installation and commissioning

#### Notes

General safety information

#### NOTICE: Observe installation and safety instructions!

- Nur von Elektrofachkraft oder einer für die Tätigkeit elektrisch unterwiesenen Person (EUP nach DIN VDE 0105-100) anzuwenden!
- Nicht unter Spannung/Last installieren!
- Nur für bestimmungsgemäßen Gebrauch einsetzen!
- Nationale Vorschriften/Normen/Richtlinien beachten!
- Technische Daten der Produkte beachten!
- Auf die richtige Polbelegung achten!
- Keine beschädigten/verschmutzten Komponenten verwenden!
- Leiterarten, -querschnitte, Abisolierlängen und Leitungsdurchmesser beachten!
- Leiter bis zum Anschlag einführen!
- Nur mit Verriegelungsklinke und Zugentlastung verwenden!
- Originalzubehör verwenden!

**To be sold only with installation instructions!**

### Material data

Note (material data)	<a href="#">Information on material specifications can be found here</a>
Color	black
Flammability class per UL94	V0
Fire load	0.252 MJ
Weight	10.8 g

### Environmental requirements

Processing temperature	-5 ... +40 °C
Continuous operating temperature	-35 ... +85 °C
Note on continuous operating temperature	Insulating parts for temperatures ≤ 105 °C

### Commercial data

Product Group	20 (Winsta)
PU (SPU)	5 pcs
Packaging type	Box
Country of origin	CH
GTIN	4045454006471
Customs tariff number	39269097900

### Product Classification

UNSPSC	39121321
eCl@ss 10.0	27-44-06-90
eCl@ss 9.0	27-44-06-92
ETIM 9.0	EC002863
ETIM 10.0	EC002863
ECCN	NO US CLASSIFICATION

### Environmental Product Compliance

RoHS Compliance Status	Compliant, No Exemption
------------------------	-------------------------

### Downloads

#### Environmental Product Compliance



##### Compliance Search

Environmental Product  
Compliance 895-1605



### Documentation

#### Bid Text

895-1605	19.02.2019	xml 2.57 KB	
895-1605	09.01.2015	doc 22.50 KB	

CAD/CAE-Data

CAE data

WSCAD Universe  
895-1605

