

START Downlight Eco165mm Round Surface

START eco Downlight 165 950lm 840 Surface


0054106



PRODUCT OVERVIEW

Product name	START eco Downlight 165 950lm 840 Surface
Technology	LED
Housing	PC Polycarbonate
Mount	Ceiling surface mounting
Warranty	3 years
Fixture luminous flux (lm)	950
Luminaire efficacy (lm/W)	79
Colour temperature (K)	4000
Light colour	Neutral White
CRI (Ra)	80
Colour Variation Initial (SDCM)	SDCM6
Glare control	< 28
Photobiological Risk Group	RG0
Total power consumption (W)	12
Electrical protection	Class II
LED Flickering Rate	Medium (21% - 40%)
Housing colour	RAL 9003 - Signal white
IP rating	IP20
IK rating	IK02
Product EAN number	5410288541068

PHOTOMETRY



Distance [m]	Cone diameter [m]	Illuminance [lx]
0.5	1.56 1.56	1281 103 101
1.0	3.12 3.13	324 26 25
1.5	4.67 4.69	144 11 11
2.0	6.23 6.25	81 6 6
2.5	7.79 7.82	63 4 4
3.0	9.35 9.38	49 3 3

Distance [m] Cone diameter [m] Illuminance [lx]
 C0 - C180 (half beam angle: 114.6°)
 C90 - C270 (half beam angle: 114.6°)

START Downlight Eco165mm Round Surface

START eco Downlight 165 950lm 840 Surface
0054106

TECHNICAL DRAWINGS

