

PLF-P-PK: Galvanised bracket flat for backplate elbow



Wall mounted bracket

This 3 mm full steel galvanised bracket can be used for different applications: shower & bath faucets, under sink mounting and robust anchoring

Commercial information

- Robust steel bracket
- Rigid wall attachment
- Accurate interaxis fixation
- Various depths for concealed mounting
- Free choice of any backplate fitting

Basic unit dimensions

Height	3 mm
Length	210 mm
Width	35 mm
Net weight	0.190 kg

Certificates

Applications

Potable water, Heating, Compressed air, Gas, Sanitary

Solutions

Building installations, Industry, Oil & gas, Utility

Technical characteristics

Inlay	Other	Outer pipe diameter	16 26 Millimetre
Connection facility	Other		
Connection size, connection facility	Other		
Flexible connection facility	✗		
Lock facility	Other		
FM quality mark	✗		
UL quality mark	✗		
ULC quality mark	✗		
LPCB quality mark	✗		
Suitable for steel tube	✓		
Suitable for thin-walled pipe	✓		
Suitable for stainless steel tube	✓		
Suitable for copper tube	✓		
Suitable for aluminium tube	✓		
Suitable for cast iron pipe	✓		
Suitable for plastic tube	✓		
Suitable for pipe coil	✓		
KIWA certified	✗		