

## Data Sheet | Item Number: 890-131

Locking lever; for flying leads; for tool operation; white

<https://www.wago.com/890-131>



Color: ■ white

### Locking system WINSTA® MINI

The locking system from the WINSTA® MINI product line is the intelligent solution for reliable electrical installation. You can rely on the level of quality of WINSTA® components from WAGO for your electrical installation accessories too. Due to its particularly compact dimensions, our WINSTA® MINI Pluggable Connection System with Push-in CAGE CLAMP® spring pressure connection technology is specifically suitable in very restricted spaces, i.e., for connections when very little room is available.

WINSTA® MINI solutions for your electrical installation – protected against mismatching and maintenance-free

The WINSTA® Pluggable Connection System allows pluggable electrical installation. This saves time, lowers costs, and reduces the need for servicing. Choose durability and quality – with protection against mismatching from WAGO makes the electrical installation of electrical components substantially easier.

- compact design for conductors with a cross-section up to 1.5 mm<sup>2</sup>
- quick replacement of defective units during ongoing operation

### Notes

General safety information

#### **NOTICE: Observe installation and safety instructions!**

- Nur von Elektrofachkraft oder einer für die Tätigkeit elektrisch unterwiesenen Person (EUP nach DIN VDE 0105-100) anzuwenden!
- Nicht unter Spannung/Last installieren!
- Nur für bestimmungsgemäßen Gebrauch einsetzen!
- Nationale Vorschriften/Normen/Richtlinien beachten!
- Technische Daten der Produkte beachten!
- Auf die richtige Polbelegung achten!
- Keine beschädigten/verschmutzten Komponenten verwenden!
- Leiterarten, -querschnitte, Abisolierlängen und Leitungsdurchmesser beachten!
- Leiter bis zum Anschlag einführen!
- Nur mit Verriegelungsklinke und Zugentlastung verwenden!
- Originalzubehör verwenden!

**To be sold only with installation instructions!**

## Connection Data

### Connection 1

Actuation type	Operating tool
----------------	----------------

## Physical data

Width	9 mm / 0.354 inches
Height	4.05 mm / 0.159 inches
Depth	27 mm / 1.063 inches

## Mechanical data

Suitable	for flying leads; tool operated
----------	---------------------------------

## Material data

Note (material data)	<a href="#">Information on material specifications can be found here</a>
Color	white
Insulation material (main housing)	Polyamide (PA66)
Flammability class per UL94	V0
Fire load	0.014 MJ
Weight	0.4 g

## Environmental requirements

Processing temperature	-5 ... +40 °C
Continuous operating temperature	-35 ... +85 °C
Note on continuous operating temperature	Insulating parts for temperatures ≤ 105 °C

## Commercial data

Product Group	20 (Winsta)
PU (SPU)	100 (50) pcs
Packaging type	Box
Country of origin	DE
GTIN	4045454232993
Customs tariff number	85389099990

## Product Classification

UNSPSC	39121702
eCl@ss 10.0	27-44-06-92
eCl@ss 9.0	27-44-06-92
ETIM 9.0	EC002863
ETIM 10.0	EC002863
ECCN	NO US CLASSIFICATION

**Environmental Product Compliance**

RoHS Compliance Status	Compliant, No Exemption
------------------------	-------------------------

**Approvals / Certificates**

**Approvals for marine applications**



Approval	Standard	Certificate Name
LR Lloyds Register	EN 61535	LR23317167TA

**Downloads**

**Environmental Product Compliance**

Compliance Search	
Environmental Product Compliance 890-131	↓

**Documentation**

Bid Text			
890-131	20.11.2014	doc 21.50 KB	↓
890-131	19.02.2019	xml 2.62 KB	↓

**CAD/CAE-Data**

CAD data	
2D/3D Models 890-131	↓

CAE data	
WSCAD Universe 890-131	↓
ZUKEN Portal 890-131	↓

Subject to changes. Please also observe the further product documentation!

Current addresses can be found at: [www.wago.com](http://www.wago.com)