Product Data Sheet
GW70206
70 RT HP-serie

70 RT HP is a complete offer of rotary isolator switches from 16 A to 160 A, available in boxes both in insulating material and aluminium, in control or emergency versions, compatible with the main applications for residential, tertiary and industrial contexts.
DC versions for photovoltaic applications are also available from 16 A to 40 A in insulating box.
The series is completed with versions for board from 16 A to 1000 A and for DIN rail fixing from 16 A to 63 A, which can be equipped with auxiliary contacts.
The devices have been designed to reduce wiring time, facilitate installation and guarantee the maximum safety and robustness even in the most demanding conditions.

ELEKTRISCHE KENMERKEN	-	**Functionele kenmerken**	-
Installatieautomaat	Roterende lastscheider	Versie	Voor bevestiging op DIN-rail
Nominale stroom (A)	32	Aant. modules EN 50022	4
Aant. polen	4P	Type	Bedieningsapparaten
Stroom bij AC21A (415 V)	32	Kleur knop	Zwart
Stroom in AC22A (415V)	32	Vergrendelbaar	Aant.
Stroom in AC23A (415V)	32	**ACCESSORIES**	-
Kabel sectie	1-10 mm²	Type accessoire	Max. 2 hulpcontacten (1 per zijde)

DIMENSIONAL



STANDARDS/APPROVALS

CE