

Data Sheet | Item Number: 897-260

Flat cable end cover; for flat cable 5 x 2.5 mm² + 2 x 1.5 mm²; Plastic; transparent

<https://www.wago.com/897-260>



Color: transparent

Cover WINSTA® IDC

Implement the electrical installation without difficulty: The cover from the WINSTA® IDC product line is the product of your choice for error-free electrical installation. A comprehensive range of accessories complements the WINSTA® product line from WAGO.

Push-in CAGE CLAMP® spring pressure connection technology – pluggable installation instead of laborious screw connections!

The WINSTA® Pluggable Connection System allows pluggable electrical installation. This significantly reduces the need for servicing and lowers costs. Now you can also cut installation expenses without compromising quality and safety: with protection against mismatching eliminates the need for servicing and prevents unnecessary downtime.

- saves time, since no wiring is required at the construction site
- convenient installation and commissioning

Notes

General safety information

NOTICE: Observe installation and safety instructions!

- Nur von Elektrofachkraft oder einer für die Tätigkeit elektrisch unterwiesenen Person (EUP nach DIN VDE 0105-100) anzuwenden!
- Nicht unter Spannung/Last installieren!
- Nur für bestimmungsgemäßen Gebrauch einsetzen!
- Nationale Vorschriften/Normen/Richtlinien beachten!
- Technische Daten der Produkte beachten!
- Auf die richtige Polbelegung achten!
- Keine beschädigten/verschmutzten Komponenten verwenden!
- Leiterarten, -querschnitte, Abisolierlängen und Leitungsdurchmesser beachten!
- Leiter bis zum Anschlag einführen!
- Nur mit Verriegelungsklinke und Zugentlastung verwenden!
- Originalzubehör verwenden!

To be sold only with installation instructions!

Mechanical data

Variable coding	No
Suitable	for flat cable 5 x 2.5 mm ² + 2 x 1.5 mm ²

Material data

Note (material data)	Information on material specifications can be found here
Color	transparent
Insulation material (main housing)	Polyamide (PA66)
Flammability class per UL94	V0
Fire load	0.288 MJ
Weight	16.8 g

Environmental requirements

Processing temperature	-5 ... +40 °C
Continuous operating temperature	-35 ... +85 °C
Note on continuous operating temperature	Insulating parts for temperatures ≤ 105 °C

Commercial data

Product Group	20 (Winsta)
PU (SPU)	25 pcs
Packaging type	Box
Country of origin	CH
GTIN	4055143385992
Customs tariff number	39269097900

Product Classification

UNSPSC	39121421
eCl@ss 10.0	27-44-06-92
eCl@ss 9.0	27-44-06-92
ETIM 9.0	EC002863
ETIM 10.0	EC002863
ECCN	NO US CLASSIFICATION

Environmental Product Compliance

RoHS Compliance Status	Compliant, No Exemption
------------------------	-------------------------

Downloads

Environmental Product Compliance

Compliance Search

Environmental Product
Compliance 897-260



Documentation

Bid Text

897-260	19.02.2019	xml 2.60 KB	
897-260	09.01.2015	doc 22.50 KB	

CAD/CAE-Data

CAE data

WSCAD Universe 897-260	
---------------------------	---