

START Downlight Flat IP44 Dimmable 205mm Round Recessed

Start Downlight Flat 205 IP44 1750LM 840 DIM
0054123



PRODUCT OVERVIEW

Product name	Start Downlight Flat 205 IP44 1750LM 840 DIM
Technology	LED
Cap/Base	N/A
Housing	Aluminium
Mount	Ceiling recessed mounting
E-number FI	4278499
Warranty	5 years
Fixture luminous flux (lm)	1750
Luminaire efficacy (lm/W)	103
Colour temperature (K)	4000
Light colour	Cool White
CRI (Ra)	80
Colour Variation Initial (SDCM)	SDCM3
Glare control	< 28
Photobiological Risk Group	RG0
Total power consumption (W)	17
Electrical protection	Class II
Control gear type	LED driver constant current
LED Flickering Rate	Ultra low (5% or less)
Housing colour	RAL 9003 - Signal white
IP rating	IP44/20
IK rating	IK06
Product EAN number	5410288541235

PHOTOMETRY


START Downlight Flat IP44 Dimmable 205mm Round Recessed

Start Downlight Flat 205 IP44 1750LM 840 DIM
0054123

0.5	1.41	E07	209
	1.43	E(C90)	244
		E(C0)	238
1.0	2.82	E07	80
	2.86	E(C90)	91
		E(C0)	80
1.5	4.24	E07	53
	4.28	E(C90)	57
		E(C0)	52
2.0	5.65	E07	38
	5.71	E(C90)	43
		E(C0)	38
2.5	7.06	E07	28
	7.14	E(C90)	31
		E(C0)	28
3.0	8.47	E07	21
	8.57	E(C90)	23
		E(C0)	21

Distance [m] Core diameter [m] Illuminance [lx]

— C0 - C180 (Half beam angle: 110.9°)
 — C90 - C270 (Half beam angle: 109.4°)



TECHNICAL DRAWINGS

