

Data Sheet | Item Number: 770-383

Operating tool; 3-way; green

<https://www.wago.com/770-383>



Color: ■ green

Technical data

| | |
|--------------------|----------|
| Number of spacings | 3 -times |
|--------------------|----------|

Physical data

| | |
|-------------|------------------------|
| Depth | 143.6 mm / 5.65 inches |
| Pin spacing | 10 mm |

Mechanical data

| | |
|----------|----------------------------------|
| Suitable | for WAGO WINSTA® MIDI Connectors |
|----------|----------------------------------|

Material data

| | |
|------------------------------------|------------------|
| Color | green |
| Insulation material (main housing) | Polyamide (PA66) |
| Flammability class per UL94 | V0 |
| Fire load | 0 MJ |
| Weight | 24.5 g |

Commercial data

| | |
|-----------------------|---------------|
| Product Group | 20 (Winsta) |
| PU (SPU) | 50 (1) pcs |
| Packaging type | Bag |
| Country of origin | DE |
| GTIN | 4050821854463 |
| Customs tariff number | 82055980000 |

Product Classification

| | |
|-------------|----------------------|
| UNSPSC | 27112809 |
| eCl@ss 10.0 | 27-44-06-92 |
| eCl@ss 9.0 | 27-44-06-92 |
| ETIM 9.0 | EC002863 |
| ETIM 10.0 | EC002863 |
| ECCN | NO US CLASSIFICATION |

Environmental Product Compliance

| | |
|------------------------|-------------------------|
| RoHS Compliance Status | Compliant, No Exemption |
|------------------------|-------------------------|

| | |
|-------------------------------|---------------|
| Processing temperature (min.) | -5 °C |
| Processing temperature (max.) | 40 °C |
| Processing temperature | -5 ... +40 °C |

Approvals / Certificates

General approvals



| Approval | Standard | Certificate Name |
|--|----------|------------------|
| cURus Underwriters Laboratories Inc. | UL 1059 | E 45172 |

Downloads

Environmental Product Compliance

Compliance Search

| | |
|---|-------------------|
| Environmental Product Compliance 770-383 | ↓ |
|---|-------------------|

Documentation

Bid Text

| | | | |
|---------|------------|-----------------|-------------------|
| 770-383 | 19.02.2019 | xml 2.59 KB | ↓ |
| 770-383 | 14.01.2015 | doc 23.00 KB | ↓ |