



### Features

- Luminaire, polycarbonate housing
- Twin version, 1500mm
- Protection type IP65
- Luminous flux and light colour vary depending on LED tubes used
- To be used with T8 LED tubes
- Easy to install with stainless steel fixing brackets included for ceiling mounting
- Ideal for any industrial facilities, garages, car parks, workshops.

### Product Overview

|  |                                  |
|--|----------------------------------|
| <b>Product name</b>                    | START WATERPROOF 1500 HOUSING 2X |
| <b>Technology</b>                      | LED                              |
| <b>Cap/Base</b>                        | 2G13                             |
| <b>Housing</b>                         | PC Polycarbonate                 |
| <b>Mount</b>                           | Wall surface mounted             |
| <b>Light source included</b>           | Fixture without Lightsource      |
| <b>General application</b>             | Logistics & Industry             |
| <b>ETIM Class</b>                      | EC002892                         |
| <b>E-number FI</b>                     | 4357158                          |
| <b>Fixture luminous flux (lm)</b>      | 1                                |
| <b>Luminaire efficacy (lm/W)</b>       | 1                                |
| <b>Light colour</b>                    | N/A                              |
| <b>Colour Variation Initial (SDCM)</b> | N/A                              |
| <b>Photobiological Risk Group</b>      | Not applicable                   |
| <b>Total power consumption (W)</b>     | 0.1                              |
| <b>Electrical protection</b>           | Class II                         |
| <b>Control gear type</b>               | Not required                     |
| <b>Dimmable</b>                        | No                               |
| <b>Housing colour</b>                  | Grey                             |
| <b>IP rating</b>                       | IP65                             |

## START WATERPROOF 1500 HOUSING 2X 0047196

|                    |               |
|--------------------|---------------|
| IK rating          | IK08          |
| Product EAN number | 5410288471969 |
| Warranty           | 5 years       |
| Dimming method     | N/A           |

### Technical drawings

