



America

CERTIFICATE

No. U10 044254 0061 Rev. 00

Holder of Certificate: **ABB Stotz-Kontakt GmbH**

Eppelheimer Str. 82
69123 Heidelberg
GERMANY

Certification Mark:




Product: **Power supplies
(Switching Power Supply)**

Tested according to: UL 62368-1:2019/R:2021-10
CSA C22.2 No. 62368-1:2019/U1:2021-10

This product was voluntarily tested to the relevant safety requirements referenced on this certificate. It can be marked with the certification mark above. The mark must not be altered in any way. The certificate holder shall not transfer this certificate to third parties. This product certification system operated by TÜV SÜD America Inc. most closely resembles system 3 as defined in ISO/IEC 17067. Certification is based on the TÜV SÜD "Testing, Certification, Validation and Verification Regulations (TCVVR)". For Canadian standards TÜV SÜD America Inc. is accredited by the Standards Council of Canada to ISO/IEC 17065.

Test report no.: 081-250340-000

Date, 2025-04-11


(Watson Yang)



America

CERTIFICATE

No. U10 044254 0061 Rev. 00

Model(s): CP-E 5/3.0, CP-E 24/0.75

Brand Name(s): ABB



Parameters:

Rated input voltage:	100-240 Vac
Rated input current:	500 mA
Rated frequency:	47-63 H
Rated outputs:	See below
Protection class:	I
Max. ambient temperature:	50 °C

Remarks:

- 1) When installing, all requirements of below mentioned test standards must be fulfilled.
- 2) The equipment is evaluated for operating in altitude up to 5,000 m above the sea level.

The output rating for models are as below:

Model	Output Voltage	Output Current	Output Power
CP-E 5/3.0	5 Vdc	3 A	15 W
CP-E 24/0.75	24 Vdc	0.75 A	18 W

ZERTIFIKAT ◆ CERTIFICATE ◆ 認 證 證 書 ◆ CERTIFICADO ◆ CERTIFICAT



CERTIFICATE

No. U10 044254 0061 Rev. 00

License Condition:

1. This power supply has been judged on the basis of the required spacing is the Standard for Safety of Audio/video, information and communication technology equipment UL 62368-1:2019/R:2021-10 and CSA C22.2 No. 62368-1:2019/U1:2021-10, which covers the end-use product for which this component was designed.
2. The power supply shall be installed in compliance with mounting, spacings, casualty and segregation requirements of the ultimate application.
3. The output connector is not acceptable for field connections and is only intended for connection to the mating connector of internal wiring inside the end – use machine. The acceptability of this and the mating connector relative to secureness, insulating materials, and temperature shall be considered.
4. The component has been evaluated of use in Class I machines. An additional evaluation should be made if the component is used in other than Class I units.
5. The unit was investigated to material Group III creepage, clearance and material properties requirements.
6. The unit was investigated as pollution degree 2 equipment.
7. The power supply shall be properly bonded to the main protective earthing termination in the end product.
8. The unit is considered acceptable for use in a 50°C ambient. Consideration should be given to the need for reconducting a temperature test in the end-use equipment.
9. Consideration should be given to measuring the temperature on power electronic components, inductors and transformer windings when the power supply is installed in the end product. Transformers T1 employ Class B Insulation Systems.
10. Stability and Mechanical strength must be evaluated in the end product.
11. Language of safety markings/instructions (if user accessible in the end product) must be included in the end product documentation.