




Wide range of control devices, sockets for power supply (conforming to national and international standards) signal pick-up, climate control, comfort management, technical alarm signalling and emergency lighting management. The ChoruSmart modular devices are available in five colours, glossy white, satin white, natural beige, satin black and lacquered titanium and in various sizes from 1/2, 1, 2 and 3 modules. Thanks to the mounting supports for rectangular, square and round boxes, endless combinations can be created with the ChoruSmart range of plates.

Category	Push-button	Button key	Neutral
Symbol		O	Colour
Description	2P NO - 16 A	Voltage	Satin white
Standard	EN 60669-1	Resistance at test voltage	250 V ac
Insulation resistance	> 5 MOhm	Wiring terminals	2000 V at 50 Hz for 1 minute
Prolonged operation switch (no.of position changes)	40.000 at In 250 V ac cosφ=0,6	Thermo-pressure with ball	With screw
Glow Wire Test	850 °C	Terminal grip on cable traction	125 °C
Terminal tightening capacity stranded cables (mm ²)	min. 0,75 - max. 2x4	Terminal tightening capacity solid cables (mm ²)	> 50 N
No. modules	1	Material	min. 0,5 - max. 2x2,5
Electrocod	0130		Technopolymer

DIMENSIONAL



TECHNICAL SYMBOLOGY



STANDARDS/APPROVALS

