

CU-ACT-B24V: Act With Cable 1M, 24V



Commercial information

- Energy efficient operator: Only 1 Watt consumption.
- Adapter concept fits 99% of the existing valves and distributors.
- Patented protection in all mounting modes for leaking valves.
- Fully isolated contacts: no short-circuiting possible
- 100% waterproof
- Also available with pluggable cable.
- 24V and 230V

Basic unit dimensions

Height	55 mm
Length	1,000 mm
Width	75 mm
Net weight	0.130 kg

Certificates

Applications

Heating, Cooling, Underfloor Heating

Solutions

Underfloor heating, Building installations, Industry, Utility

Technical characteristics

Model	Wax-filled	Cable length	1 Metre
Connection to stop valve	M30 x 1.5	Operating time	210 Second
Supply voltage	24 V AC	Stroke length	4 Millimetre
Control signal	2-point	Ambient temperature	0 60 Degrees celsius
Function	Deactivated when closed NC	Nominal power	1 Voltampere
Automatic stroke recognition	✘	Max. electric power input	1 Voltampere
Protected against overvoltage	✓	Length	1000 Millimetre
Auxiliary contacts	✘	Width	75 Millimetre
With end contacts	✘	Height	55 Millimetre
First open	✓	Diameter	90 Millimetre
With position indicator	✓		
With valve adaptor	✓		
Self-adjusting travel length	✘		
Colour	White		
Degree of protection (IP)	IP54		