

CU-ACT-B230V: Act With Cable 1M, 230V



Commercial information

- Energy efficient operator: Only 1 Watt consumption.
- Adapter concept fits 99% of the existing valves and distributors.
- Patented protection in all mounting modes for leaking valves.
- Fully isolated contacts: no short-circuiting possible
- 100% waterproof
- Also available with pluggable cable.
- 24V and 230V

Basic unit dimensions

| | |
|------------|----------|
| Height | 49 mm |
| Length | 56 mm |
| Width | 44 mm |
| Net weight | 0.130 kg |

Certificates

Applications

Heating, Cooling, Underfloor Heating

Solutions

Underfloor heating, Building installations, Industry, Utility

Technical characteristics

| | | | |
|-------------------------------|----------------------------|---------------------------|----------------------|
| Model | Wax-filled | Cable length | 1 Metre |
| Connection to stop valve | Brand-dependent | Operating time | 210 Second |
| Supply voltage | 230 V AC | Stroke length | 4 Millimetre |
| Control signal | 2-point | Ambient temperature | 0 60 Degrees celsius |
| Function | Deactivated when closed NC | Nominal power | 2 Voltampere |
| Automatic stroke recognition | ✘ | Max. electric power input | 2 Voltampere |
| Protected against overvoltage | ✓ | Length | 56 Millimetre |
| Auxiliary contacts | ✘ | Width | 44 Millimetre |
| With end contacts | ✘ | Height | 49 Millimetre |
| First open | ✓ | Diameter | 44 Millimetre |
| With position indicator | ✓ | | |
| With valve adaptor | ✓ | | |
| Self-adjusting travel length | ✘ | | |
| Colour | Grey | | |
| Degree of protection (IP) | IP54 | | |