

VKPK-32: Straight Entry Piece - Press Ø32 Black



Commercial information

Straight entry piece for Pro-Flow Manifold

Basic unit dimensions

Height	39 mm
Length	77 mm
Width	39 mm
Net weight	0.063 kg

Certificates

Applications

Potable water, Heating, Cooling, Sanitary

Solutions

Building installations, Utility, Shipbuilding

Technical characteristics

Material connection 1	Polyvinylidene fluoride (PVDF)	Bend angle	90 Degrees
Material quality connection 1	Other	Bend radius	0 Millimetre
Material connection 2	Polyvinylidene fluoride (PVDF)	Outer pipe diameter connection 1	32 Millimetre
Material quality connection 2	Other	Length	77 Millimetre
Shape	Straight	Wrench width	0 Millimetre
Model	1-part	Wrench width union nut	0 Millimetre
Reducing	✗	Medium temperature (continuous)	-10 70 Degrees celsius
Eccentric	✗	Max. operating pressure at 20 °C	10 Bar
System specific	✓	Standard Dimension Ratio (SDR)	0
Main colour fitting	Black		
With buffer stud	✓		
High tensile strength	✗		
With thermal insulation	✗		
Ring stiffness class	Other		
With sealing rings/gaskets	✓		
Capped	✗		
With connection indicator	✗		
With drain valve	✗		
With de-aerator	✗		
FM quality mark	✗		
LPCB quality mark	✗		
ULC quality mark	✗		
UL quality mark	✗		
DIN-CERTCO certificate	✗		
VdS quality mark	✗		
With approval for TÜV	✗		
DVGW quality mark for gas	✗		
DVGW quality mark for water	✗		
Certified according to NF 545	✗		
KIWA certified	✗		
Gastec QA mark	✗		
KOMO certified	✗		
Gastec QA - AR 214 (H2)	✗		
Type approval according to BBR/EKS	✗		