


Walraven RapidStrut® Rail Connector G2 (BUP1000)

(H2874)

to make Strut rail fabrications



Features & benefits

- connector with pre-assembled Walraven RapidStrut® Slide nut(s)
- to make fabrication with Walraven RapidStrut® Rail
- ready-to-use pre-assembled for a quick fixing, and retains assembly in place before final tightening
- 'Direct Twist' technology for easy and secure installation
- visual guide to check the position of the slide nut
- optimized for easy installation with electrical tools
- material: metal parts made of steel 1.0332; spring(s) made of POM (polyoxymethylene), green
- product is part of the Walraven Walraven UltraProtect® 1000 system
- suitable for in- and outdoor applications
- stands min. 1,000 hours salt spray test (max. 5% red rust) according to ISO 9227

Product Number	For Rail Type	Total Height	Total Width	Total Length	Material Thickness	Heart To Heart Distance	Torque Moment For Installation
Reference Letter		H	W	L	MT	k	T inst.
Unit description		mm	mm	mm	mm	mm	Nm
665885184	41x21, 41x41, 41x51, 41x62, 41x82	31.4	40	82	4.00	41	30
665885186	41x21, 41x41, 41x51, 41x62, 41x82	31.4	40	164	4.00	41	30