


# Walraven RapidStrut® Rail Connector G2 (BUP1000)

(H2874)

to make Strut rail fabrications



## Features & benefits

- connector with pre-assembled Walraven RapidStrut® Slide nut(s)
- to make fabrication with Walraven RapidStrut® Rail
- ready-to-use pre-assembled for a quick fixing, and retains assembly in place before final tightening
- 'Direct Twist' technology for easy and secure installation
- visual guide to check the position of the slide nut
- optimized for easy installation with electrical tools
- material: metal parts made of steel 1.0332; spring(s) made of POM (polyoxymethylene), green
- product is part of the Walraven Walraven UltraProtect® 1000 system
- suitable for in- and outdoor applications
- stands min. 1,000 hours salt spray test (max. 5% red rust) according to ISO 9227

| Product Number   | For Rail Type                     | Total Height | Total Width | Total Length | Material Thickness | Heart To Heart Distance | Torque Moment For Installation |
|------------------|-----------------------------------|--------------|-------------|--------------|--------------------|-------------------------|--------------------------------|
| Reference Letter |                                   | H            | W           | L            | MT                 | k                       | T inst.                        |
| Unit description |                                   | mm           | mm          | mm           | mm                 | mm                      | Nm                             |
| 665885184        | 41x21, 41x41, 41x51, 41x62, 41x82 | 31.4         | 40          | 82           | 4.00               | 41                      | 30                             |
| 665885186        | 41x21, 41x41, 41x51, 41x62, 41x82 | 31.4         | 40          | 164          | 4.00               | 41                      | 30                             |