


Data Sheet | Item Number: 897-121

Flat cable; Eca; 2 x 1.5 mm²; PVC; 2 buses; 50 V; 1,50 mm²; light gray

<https://www.wago.com/897-121>



Color: ■ light gray



Dimensions in mm

Flat cable WINSTA® IDC 2-pole

Thanks to the flat cable from the WINSTA® IDC product line, straightforward electrical installation is guaranteed. You can rely on the level of quality of WINSTA® components from WAGO for your electrical installation accessories too. Building safety must be ensured at all times, even after the electrical installation stage. The required safety requirements in connection with EU CPR are fully satisfied by this product through fire class E.

WINSTA® IDC solutions for your electrical installation – protected against mismatching and maintenance-free

The WINSTA® Pluggable Connection System is perfectly tailored to the very strict requirements of building installation. It makes electrical installation pluggable, and thus faster, even more reliable, and error-free. Using this pre-assembled system decreases assembly times and errors during installation at the construction site. Now you can also lower installation costs without compromising quality and safety: with fire class E eliminates the need for servicing and prevents unnecessary downtime.

- saves time, since no wiring is required at the construction site
- rapid, structured electrical installation

Notes

General safety information

NOTICE: Observe installation and safety instructions!

- Nur von Elektrofachkraft oder einer für die Tätigkeit elektrisch unterwiesenen Person (EUP nach DIN VDE 0105-100) anzuwenden!
- Nicht unter Spannung/Last installieren!
- Nur für bestimmungsgemäßen Gebrauch einsetzen!
- Nationale Vorschriften/Normen/Richtlinien beachten!
- Technische Daten der Produkte beachten!
- Auf die richtige Polbelegung achten!
- Keine beschädigten/verschmutzten Komponenten verwenden!
- Leiterarten, -querschnitte, Abisolierlängen und Leitungsdurchmesser beachten!
- Leiter bis zum Anschlag einführen!
- Nur mit Verriegelungsklinke und Zugentlastung verwenden!
- Originalzubehör verwenden!

To be sold only with installation instructions!

Electrical data

Ratings per IEC/EN

| | |
|------------------|--|
| Legend (ratings) | (III / 3) Δ Overvoltage category III / Pollution degree 3 |
|------------------|--|

Connection Data

Connection 1

| | |
|--------------------|---------------------|
| Pole number | 2 |
| Wire cross-section | 1.5 mm ² |

Physical data

| | |
|--------|-----------------------|
| Width | 10.9 mm / 0.43 inches |
| Height | 6.1 mm / 0.24 inches |

Mechanical data

| | |
|-----------------|----|
| Variable coding | No |
|-----------------|----|

Plug-in connection

| | |
|----------------------|----|
| Mismating protection | No |
|----------------------|----|

Material data

| | |
|--------------------------------|--|
| Note (material data) | Information on material specifications can be found here |
| Color | light gray |
| Fire class per EN 50575 | E _{ca} |
| Fire load | 1.728 MJ |
| Silicon-free | Yes |
| Sheath material | PVC |
| Rubber cable | No |
| Weight | 90 g |
| Copper weight of the raw cable | 0.029 kg/m |

Environmental requirements

| | |
|--|---|
| Processing temperature | 5 ... 40 °C |
| Continuous operating temperature | -25 ... +70 °C |
| Note on continuous operating temperature | Insulating parts for temperatures \leq 105 °C |

Commercial data

| | |
|-----------------------|---------------|
| Product Group | 20 (Winsta) |
| PU (SPU) | 1 pcs |
| Packaging type | Box |
| Country of origin | CH |
| GTIN | 4045454267315 |
| Customs tariff number | 85444995900 |

| Product Classification | |
|------------------------|----------------------|
| UNSPSC | 26121629 |
| eCl@ss 10.0 | 27-06-01-06 |
| eCl@ss 9.0 | 27-06-20-02 |
| ETIM 9.0 | EC003250 |
| ETIM 10.0 | EC003250 |
| ECCN | NO US CLASSIFICATION |

| Environmental Product Compliance | |
|----------------------------------|-------------------------|
| RoHS Compliance Status | Compliant, No Exemption |

Downloads

Environmental Product Compliance

| Compliance Search | |
|--|-------------------|
| Environmental Product Compliance 897-121 | ↓ |

Documentation

| Additional Information | |
|------------------------|-------------------|
| pdf 518.02 KB | ↓ |

| Bid Text | | | |
|----------|------------|-----------------|-------------------|
| 897-121 | 19.02.2019 | xml 2.58 KB | ↓ |
| 897-121 | 09.01.2015 | doc 22.50 KB | ↓ |

CAD/CAE-Data

| CAE data | |
|---------------------------|-------------------|
| WSCAD Universe 897-121 | ↓ |

1 Compatible Products

1.1 Optional Accessories

1.1.1 Cover

1.1.1.1 Cover



Item No.: 897-120
Flat cable end cover; for flat cable 2 x 1.5 mm²; Plastic; transparent

Item No.: 897-900
Insulating tape for flat cable; 3-pole; black

1.1.2 Installation

1.1.2.1 Mounting accessories



Item No.: [897-878](#)

Fixing clamp for screw mounting; plastic;
gray