


ToLEDo AVANT T8 CCG and AC  
ToLEDo T8 V7 5FT 2700LM 840 RL  
0029298



Product features

- Energy efficient and affordable LED T8 solution to replace conventional fluorescent T8 lampsOmni-directional uniform light distribution thanks to glass tube construction design, same as traditional fluorescent T8 tubesHigh lumen package - 2700lmHigh lumen efficacy - 106 lm/WSwitching cycles - 200,000XAverage life 40,000 hours lifespanLamp length - 1500mmWide beam angleHigh power factorSuitable for general illumination in offices, supermarkets, department stores, train stations, petrol stations, parking lots and maintenance free applicationsSuitable for operation with electromagnetic gears / CCG and direct mains operation (220-240V)3-Year warranty




PRODUCT OVERVIEW

|                                   |                                                           |
|-----------------------------------|-----------------------------------------------------------|
| Product name                      | ToLEDo T8 V7 5FT 2700LM 840 RL                            |
| Technology                        | LED                                                       |
| Watt (Rated) (W)                  | 25.5                                                      |
| Lamp shape                        | Tube, double-ended                                        |
| Cap/Base                          | G13                                                       |
| Lamp finish                       | Opal                                                      |
| Fixture rating                    | Open                                                      |
| General application               | Hospitality, Logistics & Industry, Residential & Consumer |
| ETIM Class                        | EC001959                                                  |
| E-number FI                       | 4941317                                                   |
| Warranty                          | 3 years                                                   |
| Useful luminous flux (Fuse)       | 2700                                                      |
| Luminous flux (lm)                | 2700                                                      |
| Correlated colour temperature (k) | 4000                                                      |
| Light colour                      | Cool White                                                |
| CRI (Ra)                          | 80                                                        |
| Colour Variation Initial (SDCM)   | SDCM6                                                     |
| Beam Angle (°)                    | 170                                                       |
| Photobiological Risk Group        | RG0                                                       |
| Power consumption (W)             | 25.5                                                      |
| Wattage (W)                       | 25.5                                                      |
| Dimmable                          | No                                                        |
| Average life (Nominal) (h)        | 40000                                                     |
| IP rating                         | IP20                                                      |
| Product EAN number                | 5410288292984                                             |

PHOTOMETRY

## ToLEDo AVANT T8 CCG and AC

*ToLEDo T8 V7 5FT 2700LM 840 RL*  
0029298



## TECHNICAL DRAWINGS

