


Walraven BISMAT® 2000 'S' (M8/M10) 2-screw

(A0536)

for steam pipes



Features & benefits

- two-screw clamp
- with Walraven BISMAT® quick locking system
- clamp easy to close with one hand
- material: steel
- zinc plated
- sound insulating lining according DIN 4109
- tested for fire safety
- heat resistant up to 210°C



EPD

Product Number	Outside Pipe Diameter	DN	Pipe Diameter Imperial	Connection Thread	Total Width x Total Height x Total Depth	Material Width x Material Thickness	Screw Size	Approvals	Maximum Allowed Load Faz
Reference letter	D	D	D	G	W x H x DtT	MW x MT	ds		F _{0,z}
Unit description	mm		"		mm x mm x mm	mm x mm			N
3404080	73 - 80	DN 65	2½	M8/M10	126 x 109 x 23	23 x 2.00	M6	ITB (KOT) EPD	930
3404091	83 - 91	DN 80	3	M8/M10	137 x 121 x 25	25 x 2.50	M6	ITB (KOT) EPD	930
3404114	108 - 114	DN 100	4	M8/M10	160 x 141 x 25	25 x 2.50	M6	ITB (KOT) EPD	930
3404141	133 - 141	DN 125	5	M8/M10	189 x 170 x 25	25 x 2.50	M6	ITB (KOT) EPD	930
3404168	159 - 168	DN 150	6	M10	233 x 198 x 25	25 x 3.00	M8	ITB (KOT) EPD	930