

47P-20H20: Transition Coupling U-TH-H 20x2,25mm to Henco 20x2,0



Commercial information

Basic unit dimensions

Height	27 mm
Length	64 mm
Width	27 mm
Net weight	0.068 kg

Certificates

KIWA

Applications

Potable water, Heating, Cooling, Compressed air, Sanitary

Solutions

Building installations, Utility, Shipbuilding, Industry

Technical characteristics

Material connection 1	Brass	Bend radius	0 Millimetre
Surface protection connection 1	Untreated	Outer pipe diameter connection 1	20 Millimetre
Surface treatment connection 1	Untreated	Outer pipe diameter connection 2	20 Millimetre
Material connection 2	Brass	Length	27 Millimetre
Surface protection connection 2	Untreated	Medium temperature (continuous)	-10 70 Degrees celsius
Surface treatment connection 2	Untreated	Max. operating pressure at 20 °C	16 Bar
Shape	Straight	Max. operating pressure at max. medium temperature	16 Bar
Model	1-part		
Reducing	✘		
Eccentric	✘		
System specific	✘		
Connection 1	Press sleeve		
Connection 2	Press sleeve		
Contour code connection 2	TH		
Main colour fitting	Brass		
Material sealing	Ethylene-propylene diene monomer rubber (EPDM)		
With buffer stud	✓		
With thermal insulation	✘		
With sealing rings/gaskets	✓		
Capped	✘		
With connection indicator	✓		
With drain valve	✘		
With de-aerator	✘		
FM quality mark	✘		
LPCB quality mark	✘		
ULC quality mark	✘		
UL quality mark	✘		
DIN-CERTCO certificate	✘		
VdS quality mark	✘		
With approval for TÜV	✘		
DVGW quality mark for gas	✘		
DVGW quality mark for water	✓		
Certified according to NF 545	✘		
KIWA certified	✓		
Gastec QA mark	✘		
KOMO certified	✓		
Gastec QA - AR 214 (H2)	✘		
Type approval according to BBR/EKS	✘		