

ZODIAC MEDIUM G2 21KLM 4000K CLI GREY
0049982



Features

• The Zodiac family is dedicated for road/area lighting applications. Light distribution: Asymmetric Medium for roads, color temperature: 4000K , total system power: 148W, total fixture lumen output: 20600lm, luminaire efficacy: 139lm/W, colour rendering index: 70, LED Chromaticity: 5 step MacAdam ellipse tolerance, lumen maintenance: 50000 hours at L70:B50 @ 25°C, operating voltage: 220-240V / 50-60Hz, operating temperature range: -35 - +45°C, non-dimmable, power factor: min. 0.9, electrical protection: Class I, Ingress protection rating: IP66, Impact resistance: IK08, dimensions (LxWxH): 675x292x101mm, net weight: 6.2kg, for 42-60mm side entry or post top installation with +/-15° adjustability, the housing is made of Die Cast Aluminium in RAL9022 color combined with tempered flat glass cover.


Product Overview

Product name	ZODIAC MEDIUM G2 21KLM 4000K CLI GREY
Technology	LED
Cap/Base	N/A
Housing	Aluminium
General application	Education, Hospitality, Logistics & Industry, Office, Retail
ETIM Class	EC000062
E-number FI	4579578
Fixture luminous flux (lm)	20600
Luminaire efficacy (lm/W)	139
Correlated colour temperature (k)	4000
Light colour	Neutral White
CRI (Ra)	70
Colour Variation Initial (SDCM)	5
Photobiological Risk Group	RG1

ZODIAC MEDIUM G2 21KLM 4000K CLI GREY
0049982

Total power consumption (W)	148
Electrical protection	Class I
LED Flickering Rate	Ultra low (5% or less)
Housing colour	Grey
IP rating	IP66
IK rating	IK08
Product EAN number	5410288499826
Warranty	5 years
Useful luminous flux (#use)	20600

Photometry



Technical drawings

