
epd-global
Powered by EPD-Norway

Environmental product declaration

in accordance with ISO 14025 and EN 15804+A2

KSV



systemair

EPD-Global

Owner of the declaration:
Systemair Production a.s.

Product:
KSV

Declared unit:
1 pcs

This declaration is based on Product Category Rules:
CEN Standard EN 15804:2012+A2:2019 serves as core PCR
NPCR 030:2021 Part B for ventilation components

Program operator:
EPD-Global

Declaration number:
NEPD-8096-7793

Issue date:
14.11.2024

Valid to:
14.11.2029

EPD software:
LCAno EPD generator ID: 292164

General information

Product

KSV

Owner of the declaration:

Systemair Production a.s.
Contact person: Peter Sopkuliak
Phone: +421 2 4020 3111
e-mail: production@systemair.sk

Program operator:

EPD-Global
Post Box 5250 Majorstuen, 0303 Oslo, Norway
Phone: +47 977 22 020
web: www.epd-global.com

Manufacturer:

Systemair Production a.s.

Declaration number:

NEPD-8096-7793

Place of production:

Systemair Production a.s.
Hlavná 371
900 43 Kalinkovo, Slovakia

This declaration is based on Product Category Rules:

CEN Standard EN 15804:2012+A2:2019 serves as core PCR
NPCR 030:2021 Part B for ventilation components

Management system:

ISO 9001, ISO 14001

Statement of liability:

The owner of the declaration shall be liable for the underlying information and evidence. EPD-Global shall not be liable with respect to manufacturer information, life cycle assessment data and evidences.

Organisation no:

SK2020363290

Declared unit:

1 pcs KSV

Issue date:

14.11.2024

Declared unit with option:

A1-A3, A4, C1, C2, C3, C4, D

Valid to:

14.11.2029

Year of study:

2023

Functional unit:

Not declared

Comparability:

EPDs of construction products may not be comparable if they do not comply with EN 15804 and are not viewed in a building context.

General information on verification of EPD from EPD tools:

Independent verification of data, other environmental information and the declaration according to ISO 14025:2010, § 8.1.3 and § 8.1.4. Verification of each EPD is made according to EPD-Global's guidelines for verification and approval requiring that tools are i) integrated into the company's environmental management system, ii) the procedures for use of the EPD tool are approved by EPD-Global, and iii) the process is reviewed annually by an independent third party verifier. See Appendix G of EPD-Global's General Programme Instructions for further information on EPD tools

Development and verification of EPD:

The declaration is created using EPD tool lca.tools ver EPD2022.03, developed by LCA.no. The EPD tool is integrated in the company's management system, and has been approved by EPD-Global. Approval number:

Developer of EPD: Peter Sopkuliak

Reviewer of company-specific input data and EPD: Adam Began - INACTIVE

Verification of EPD tool:


Independent third party verification of the EPD tool, background data and test-EPD in accordance with EPD-Global's procedures and guidelines for verification and approval of EPD tools.

Third party verifier:

Alexander Borg, Asplan Viak AS

(no signature required)

Approved:



Håkon Hauan, CEO EPD-Global

Product

Product description:

KSV is a slot diffuser with adjustable deflectors, primarily designated for air supply.

Product specification

The KSV linear diffusers are available in various options and sizes.
Specific EPD data is provided as a reference for the KSV-2-1050-B-0-AN model.
Correction factors for other sizes can be estimated using the table in the Technical Data section below.

Materials	kg	%
Metal - Aluminium	1.90	95.04
Metal - Steel	0.032	1.60
Plastic - Polyethylene	0.006629	0.3314
Plastic - Polypropylene (PP)	0.06066	3.03
Total	2.00	100.00

Packaging	kg	%
Packaging - Cardboard	0.04326	29.85
Packaging - label, supercalendered	0.007	4.83
Packaging - Plastic	0.0243	16.77
Packaging - Wood	0.07034	48.54
Total incl. packaging	2.14	100.00

Technical data:

Technical details can be found at the following link:
https://design.systemair.com.

To estimate the Global Warming Potential (GWPtot) correction factor for specific product sizes, refer to the table below.

Product	Size	Weight (kg)	GWP-total (A1-A3) (kg CO2 eq)	Factor (-)
KSV	1	1,55	20,71	0,706
KSV	2	2,14	29,34	1
KSV	3	3,95	55,77	1,901
KSV	4	5,13	72,89	2,485
PB-KSV	1	6,49	9,38	0,32
PB-KSV	2	8,49	13,01	0,444
PB-KSV	3	9,49	14,82	0,505
PB-KSV	4	12,89	20,93	0,713

Market:

Europe.

Reference service life, product

Dependent on the application of the product.

Reference service life, building or construction works

Not declared.

LCA: Calculation rules

Declared unit:

1 pcs KSV

Cut-off criteria:

All major raw materials and all the essential energy is included. The production processes for raw materials and energy flows with very small amounts (less than 1%) are not included. These cut-off criteria do not apply for hazardous materials and substances.

Allocation:

The allocation is made in accordance with the provisions of EN 15804. Energy, water and waste production in-house is allocated equally among all products through mass allocation. Effects of primary production of recycled materials is allocated to the main product in which the material was used. The recycling process and transportation of the material is allocated to this analysis.

Data quality:


Specific data for the product composition are provided by the manufacturer. The data represent the production of the declared product and were collected for EPD development in the year of study. Background data is based on EPDs according to EN 15804 and different LCA databases. The data quality of the raw materials in A1 is presented in the table below.

Materials	Source	Data quality	Year
Metal - Aluminium	Modified ecoinvent 3.6	Database	2019
Metal - Steel	ecoinvent 3.6	Database	2019
Packaging - Cardboard	ecoinvent 3.6	Database	2019
Packaging - label, supercalendered	Ecoinvent 3.6	Database	2019
Packaging - Plastic	ecoinvent 3.6	Database	2019
Packaging - Wood	Modified ecoinvent 3.6	Database	2019
Plastic - Polyethylene	ecoinvent 3.6	Database	2019
Plastic - Polypropylene (PP)	ecoinvent 3.6	Database	2019

System boundaries (X=included, MND=module not declared, MNR=module not relevant)

Product stage			Construction installation stage		Use stage							End of life stage				Beyond the system boundaries
Raw materials	Transport	Manufacturing	Transport	Assembly	Use	Maintenance	Repair	Replacement	Refurbishment	Operational energy use	Operational water use	De-construction demolition	Transport	Waste processing	Disposal	Reuse-Recovery-Recycling-potential
A1	A2	A3	A4	A5	B1	B2	B3	B4	B5	B6	B7	C1	C2	C3	C4	D
X	X	X	X	MND	MND	MND	MND	MND	MND	MND	MND	X	X	X	X	X

System boundary:



Additional technical information:

For comprehensive technical information and documentation, please refer to the official Systemair website at https://www.systemair.com or the dedicated product-specific site at https://design.systemair.com.

LCA: Scenarios and additional technical information

The following information describe the scenarios in the different modules of the EPD.

For A4 and C2, a generic transportation distance (EURO6 truck) of 300 km and 50 km, respectively, is declared. The true transportation distance can be provided in the project-specific EPD.

Transport from production place to user (A4)	Capacity utilisation (incl. return) %	Distance (km)	Fuel/Energy Consumption	Unit	Value (Liter/tonne)
Truck, 16-32 tonnes, EURO 6 (km)	36.7 %	300.00	0.043	l/tkm	12.90

De-construction demolition (C1)	Unit	Value			
Demolition of building per kg of ventilation product (kg)	kg/DU	2.00			

Transport to waste processing (C2)	Capacity utilisation (incl. return) %	Distance (km)	Fuel/Energy Consumption	Unit	Value (Liter/tonne)
Truck, 16-32 tonnes, EURO 6 (km)	36.7 %	50.00	0.043	l/tkm	2.15

Waste processing (C3)	Unit	Value			
Materials to recycling (kg)	kg	1.80			
Waste treatment per kg Polyethylene (PE), incineration (kg)	kg	0.003314			
Waste treatment per kg Polypropylene (PP), incineration (kg)	kg	0.03033			

Disposal (C4)	Unit	Value			
Waste, scrap zinc, to landfill (kg)	kg	0.0032			
Waste, plastic, mixture, to landfill (kg)	kg	0.03364			
Landfilling of ashes from incineration of Polyethylene (PE), process per kg ashes and residues (kg)	kg	0.0001168			
Landfilling of ashes from incineration of Polypropylene (PP), process per kg ashes and residues (kg)	kg	0.0009027			
Waste, aluminium, to landfill (kg)	kg	0.133			

Benefits and loads beyond the system boundaries (D)	Unit	Value			
Substitution of primary steel with net scrap (kg)	kg	0.0288			
Substitution of electricity (MJ)	MJ	0.0558			
Substitution of thermal energy, district heating (MJ)	MJ	0.8441			
Substitution of primary aluminium with net scrap (kg)	kg	0.133			

LCA: Results

The LCA results are presented below for the declared unit defined on page 2 of the EPD document.

Environmental impact									
	Indicator	**Unit**	A1-A3	A4	C1	C2	C3	C4	D
	GWP-total	kg CO_2 -eq	2.93E+01	1.05E-01	2.64E-03	1.75E-02	8.73E-02	5.83E-03	-1.25E+00
	GWP-fossil	kg CO_2 -eq	2.92E+01	1.05E-01	2.64E-03	1.75E-02	8.73E-02	5.82E-03	-1.22E+00
	GWP-biogenic	kg CO_2 -eq	9.43E-02	4.35E-05	4.94E-07	7.25E-06	7.19E-07	6.49E-06	-5.46E-03
	GWP-luluc	kg CO_2 -eq	6.91E-02	3.74E-05	2.08E-07	6.24E-06	1.09E-07	8.30E-07	-2.26E-02
	ODP	kg CFC11 -eq	3.05E-06	2.38E-08	5.70E-10	3.97E-09	6.90E-11	6.52E-10	-3.57E-04
	AP	mol H+ -eq	2.00E-01	3.02E-04	2.76E-05	5.03E-05	1.10E-05	1.78E-05	-8.20E-03
	EP-FreshWater	kg P -eq	2.74E-03	8.40E-07	9.60E-09	1.40E-07	7.25E-09	3.90E-08	-4.81E-05
	EP-Marine	kg N -eq	2.24E-02	5.98E-05	1.22E-05	9.96E-06	5.26E-06	1.04E-05	-1.06E-03
	EP-Terrestial	mol N -eq	2.53E-01	6.69E-04	1.34E-04	1.11E-04	5.69E-05	7.15E-05	-1.16E-02
	POCP	kg NMVOC -eq	8.15E-02	2.56E-04	3.67E-05	4.27E-05	1.37E-05	2.11E-05	-3.94E-03
	ADP-minerals&metals[1]	kg Sb-eq	1.56E-04	2.90E-06	4.05E-09	4.84E-07	3.18E-09	1.75E-08	1.22E-06
	ADP-fossil[1]	MJ	5.29E+02	1.59E+00	3.63E-02	2.65E-01	5.89E-03	5.27E-02	-1.54E+01
	WDP[1]	m^3	7.85E+03	1.54E+00	7.71E-03	2.56E-01	1.37E-02	1.21E+00	-6.76E+02

GWP-total = Global Warming Potential total; GWP-fossil = Global Warming Potential fossil fuels; GWP-biogenic = Global Warming Potential biogenic; GWP-luluc = Global Warming Potential land use and land use change; ODP = Depletion potential of the stratospheric ozone layer; AP = Acidification potential, Accumulated Exceedance; EP-freshwater = Eutrophication potential, fraction of nutrients reaching freshwater end compartment: EP-marine = Eutrophication potential, fraction of nutrients reaching marine end compartment; EP-terrestrial = Eutrophication potential, Accumulated Exceedance; POCP = Formation potential of tropospheric ozone; ADP-minerals&metals = Abiotic depletion potential for non-fossil resources; ADP-fossil = Abiotic depletion for fossil resources potential; WDP = Water (user) deprivation potential, deprivation-weighted water consumption

"Reading example: 9.0 E-03 = 9.0*10-3 = 0.009"

1. The results of this environmental impact indicator shall be used with care as the uncertainties on these results are high or as there is limited experienced with the indicator

Remarks to environmental impacts

Air distribution components directly affect the pressure drop / energy efficiency of the ventilation system and consequently the operational energy use of the building. To properly evaluate the environmental performance and impact of the product, these factors must be taken into account.

Additional environmental impact indicators									
Indicator		Unit	A1-A3	A4	C1	C2	C3	C4	D
	PM	Disease incidence	1.35E-06	6.44E-09	7.30E-10	1.07E-09	5.10E-11	3.13E-10	-8.76E-08
	IRP[2]	kgBq U235 -eq	4.06E+00	6.95E-03	1.56E-04	1.16E-03	1.02E-05	3.37E-04	-6.57E-02
	ETP-fw[1]	CTUe	4.41E+02	1.18E+00	1.98E-02	1.96E-01	1.74E-02	8.24E+01	-2.00E+01
	HTP-c[1]	CTUh	5.30E-08	0.00E+00	0.00E+00	0.00E+00	2.00E-12	4.00E-12	-3.15E-09
	HTP-nc[1]	CTUh	8.17E-07	1.29E-09	1.80E-11	2.14E-10	7.40E-11	7.40E-11	-3.19E-08
	SQP[1]	dimensionless	9.12E+01	1.11E+00	4.61E-03	1.85E-01	7.40E-04	1.56E-01	-6.16E-01

PM = Particulate Matter emissions; IRP = Ionizing radiation – human health; ETP-fw = Eco toxicity – freshwater; HTP-c = Human toxicity – cancer effects; HTP-nc = Human toxicity – non cancer effects; SQP = Potential Soil Quality Index (dimensionless)

"Reading example: 9.0 E-03 = 9.0*10-3 = 0.009"

1. The results of this environmental impact indicator shall be used with care as the uncertainties on these results are high or as there is limited experienced with the indicator
2. This impact category deals mainly with the eventual impact of low dose ionizing radiation on human health of the nuclear fuel cycle. It does not consider effects due to possible nuclear accidents, occupational exposure nor due to radioactive waste disposal in underground facilities. Potential ionizing radiation from the soil, from radon and from some construction materials is also not measured by this indicator.

Resource use									
Indicator		Unit	A1-A3	A4	C1	C2	C3	C4	D
	PERE	MJ	3.86E+01	2.27E-02	1.96E-04	3.79E-03	1.78E-04	6.56E-03	-5.89E+00
	PERM	MJ	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00
	PERT	MJ	3.86E+01	2.27E-02	1.96E-04	3.79E-03	1.78E-04	6.56E-03	-5.89E+00
	PENRE	MJ	5.26E+02	1.59E+00	3.63E-02	2.65E-01	5.89E-03	5.27E-02	-1.54E+01
	PENRM	MJ	2.27E+00	0.00E+00	0.00E+00	0.00E+00	-2.27E+00	0.00E+00	0.00E+00
	PENRT	MJ	5.28E+02	1.59E+00	3.63E-02	2.65E-01	-2.26E+00	5.27E-02	-1.54E+01
	SM	kg	1.56E-02	0.00E+00	1.78E-05	0.00E+00	0.00E+00	0.00E+00	0.00E+00
	RSF	MJ	1.66E+00	8.14E-04	4.83E-06	1.36E-04	4.92E-06	1.36E-04	-1.15E-03
	NRSF	MJ	8.77E-01	2.91E-03	7.11E-05	4.85E-04	0.00E+00	1.92E-04	1.57E-02
	FW	m^3	5.69E-01	1.70E-04	1.87E-06	2.83E-05	1.63E-05	6.84E-05	-3.03E-02

PERE = Use of renewable primary energy excluding renewable primary energy resources used as raw materials; PERM = Use of renewable primary energy resources used as raw materials; PERT = Total use of renewable primary energy resources; PENRE = Use of non renewable primary energy excluding non-renewable primary energy resources used as raw materials; PENRM = Use of non renewable primary energy resources used as raw materials; PENRT = Total use of non renewable primary energy resources; SM = Use of secondary materials; RSF = Use of renewable secondary fuels; NRSF = Use of non-renewable secondary fuels; FW = Net use of fresh water

"Reading example: 9.0 E-03 = 9.0*10-3 = 0.009"

End of life - Waste									
Indicator		Unit	A1-A3	A4	C1	C2	C3	C4	D
	HWD	kg	8.10E-02	8.20E-05	1.07E-06	1.37E-05	0.00E+00	8.63E-04	4.81E-03
	NHWD	kg	6.22E+00	7.73E-02	4.30E-05	1.29E-02	0.00E+00	1.70E-01	-3.58E-01
	RWD	kg	3.53E-03	1.08E-05	2.52E-07	1.80E-06	0.00E+00	5.40E-08	-6.17E-05

HWD = Hazardous waste disposed; NHWD = Non-hazardous waste disposed; RWD = Radioactive waste disposed

"Reading example: 9.0 E-03 = 9.0*10-3 = 0.009"

End of life - Output flow									
Indicator		Unit	A1-A3	A4	C1	C2	C3	C4	D
	CRU	kg	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00
	MFR	kg	6.37E-01	0.00E+00	1.75E-05	0.00E+00	1.80E+00	3.02E-06	0.00E+00
	MER	kg	3.10E-02	0.00E+00	5.43E-08	0.00E+00	3.36E-02	7.38E-08	0.00E+00
	EEE	MJ	1.53E-02	0.00E+00	1.86E-07	0.00E+00	5.58E-02	4.79E-06	0.00E+00
	EET	MJ	2.32E-01	0.00E+00	2.81E-06	0.00E+00	8.44E-01	7.24E-05	0.00E+00

CRU = Components for re-use; MFR = Materials for recycling; MER = Materials for energy recovery; EEE = Exported energy electrical; EET = Exported energy thermal

"Reading example: 9.0 E-03 = 9.0*10-3 = 0.009"

Biogenic Carbon Content		
Indicator	Unit	At the factory gate
Biogenic carbon content in product	kg C	0.00E+00
Biogenic carbon content in accompanying packaging	kg C	0.00E+00

Note: 1 kg biogenic carbon is equivalent to 44/12 kg CO2

Additional requirements

Greenhouse gas emissions from the use of electricity in the manufacturing phase

National production mix from import, low voltage (production of transmission lines, in addition to direct emissions and losses in grid) of applied electricity for the manufacturing process (A3).

Electricity mix	Source	Amount	Unit
Electricity, Slovakia (kWh)	ecoinvent 3.6	519.35	g CO2-eq/kWh
Electricity, Solar, Slovakia (kWh)	ecoinvent 3.6	91.57	g CO2-eq/kWh

Dangerous substances

The product contains no substances on the REACH Candidate list at or above 100 ppm, 0,01 % by weight.

Indoor environment

Air distribution products are essential in creating good indoor environments. Proper air distribution is a determining factor for ventilation efficiency, achieving thermal comfort and good indoor air quality.

Additional Environmental Information

Additional environmental impact indicators required in NPCR Part A for construction products								
Indicator	**Unit**	A1-A3	A4	C1	C2	C3	C4	D
GWPIOBC	kg CO_2 -eq	2.93E+01	1.05E-01	2.64E-03	1.75E-02	8.73E-02	5.83E-03	-1.21E+00

GWP-IOBC: Global warming potential calculated according to the principle of instantaneous oxidation. In order to increase the transparency of biogenic carbon contribution to climate impact, the indicator GWP-IOBC is required as it declares climate impacts calculated according to the principle of instantaneous oxidation. GWP-IOBC is also referred to as GWP-GHG in context to Swedish public procurement legislation.

Bibliography

ISO 14025:2010 Environmental labels and declarations - Type III environmental declarations - Principles and procedures.
ISO 14044:2006 Environmental management - Life cycle assessment - Requirements and guidelines.
EN 15804:2012+A2:2019 Environmental product declaration - Core rules for the product category of construction products.
ISO 21930:2017 Sustainability in buildings and civil engineering works - Core rules for environmental product declarations of construction products.
ecoinvent v3, Allocation, cut-off by classification, Swiss Centre of Life Cycle Inventories.
Iversen et al., (2021) eEPD v2021.09 Background information for EPD generator tool system verification, LCA.no Report number: 07.21
Graafland and Iversen (2022) EPD generator for NPCR 030 Ventilation components, Background information for EPD generator application and LCA data, LCA.no report number: 12.22
NPCR Part A: Construction products and services. Ver. 2.0. April 2021, EPD-Norge.
NPCR 030 Part B for Ventilation components, Ver. 1.0, 18.05.2021, EPD Norway.

epd-global Powered by EPD-Norway	**Program operator and publisher** EPD-Global Postboks 5250 Majorstuen, 0303 Oslo, Norway	Phone: e-mail: web:	+47 977 22 020 post@epd-norge.no www.epd-global.com
systemair	**Owner of the declaration:** Systemair Production a.s. Hlavná 371, 900 43 Kalinkovo, Slovakia	Phone: e-mail: web:	+421 2 4020 3111 production@systemair.sk www.systemair.com/sk
LCA.no	**Author of the Life Cycle Assessment** LCA.no AS Dokka 6A, 1671 Kråkerøy, Norway	Phone: e-mail: web:	+47 916 50 916 post@lca.no www.lca.no
LCA.no	**Developer of EPD generator** LCA.no AS Dokka 6A, 1671 Kråkerøy, Norway	Phone: e-mail: web:	+47 916 50 916 post@lca.no www.lca.no
ECO PLATFORM EPD VERIFIED	ECO Platform ECO Portal	web: web:	www.eco-platform.org ECO Portal