


ZODIAC SMALL G2 7KLM 4000K CLI GREY


Item No: 0049970




The Zodiac family is dedicated for road/area lighting applications. Light distribution: Asymmetric Medium for roads, color temperature: 4000K , total system power: 54W, total fixture lumen output: 7400lm, luminaire efficacy: 137lm/W, colour rendering index: 70, LED Chromaticity: 5 step MacAdam ellipse tolerance, lumen maintenance: 50000 hours at L70:B50 @ 25°C, operating voltage: 220-240V / 50-60Hz, operating temperature range: -35 - +45°C, non-dimmable, power factor: min. 0.9, electrical protection: Class I, Ingress protection rating: IP66, Impact resistance: IK08, dimensions (LxWxH): 573x182x103mm, net weight: 3.4kg, for 42-60mm side entry or post top installation with +/-15° adjustability, the housing is made of Die Cast Aluminium in RAL9022 color combined with tempered flat glass cover.

Technical Assets

Dimensions (mm)



Photometrics



ZODIAC SMALL G2 7KLM 4000K CLI GREY

Item No: 0049970

SYLVANIA

General data

Product name	ZODIAC SMALL G2 7KLM 4000K CLI GREY
Technology	LED
Accessory type	Mounting
Cap/Base	N/A
Housing	Aluminium
General application	Education, Hospitality, Logistics & Industry, Office, Retail
Operating temperature range (°C)	-35°C...+45°C
Performance ambient temperature Tq (°C)	25
ETIM Class	EC000062
E-number FI	4579575
Warranty	5 years

Optical data

Useful luminous flux (Φuse)	7400
Fixture luminous flux (lm)	7400
Luminaire efficacy (lm/W)	137
Correlated colour temperature (k)	4000
Light colour	Neutral White
CRI (Ra)	70
Colour Variation Initial (SDCM)	SDCM5
Distribution type	Asymmetric
Photobiological Risk Group	RG1

Electrical data

Total power consumption (W)	54
Primary Supply/Product voltage - min (V)	220
Primary Supply/Product voltage - max (V)	240
Electrical protection	Class I
Drive current (mA)	530
Inrush Current (A)	53
Inrush Duration (µs)	200
Energy Efficiency Class (A->G) of contained light source	D
Nominal Frequency (Hz)	50/60Hz
LED Flickering Rate	Ultra low (5% or less)
Max. products per 10A C Breaker	10
Max. products per 13A C Breaker	13
Max. products per 16A C Breaker	16
Max. products per 20A C Breaker	20
Max. products per 10A B Breaker	7
Max. products per 13A B Breaker	9
Max. products per 16A B Breaker	12
Max. products per 20A B Breaker	14
Mains surge immunity (differential mode -> L-N) (kV)	10
Mains surge immunity (common mode -> L/N - GND) (kV)	10

Lifetime data

Lifespan L70 B50	50000
------------------	-------

ZODIAC SMALL G2 7KLM 4000K CLI GREY

Item No: 0049970



Physical data

Housing colour	Grey
IP rating	IP66
IK rating	IK08
Diffuser finish	Transparent
Diffuser material	Glass
Nominal Product Length (mm)	573
Nominal Product Width (mm)	182
Nominal Product Height (mm)	103
Weight (kg)	3.4

Packaging

Product EAN number	5410288499703
Packaging single length / height (cm)	58.5
Packaging single width (cm)	19.5
Packaging single depth (cm)	12.8
DUN14 (inner)	05410288499703
Units per outer package	1
Packaging outer length / height (cm)	58.5
Packaging outer width (cm)	19.5
Packaging outer depth (cm)	12.8

Safety data

Glow Wire Test (°C)	650
Optimal operating condition (°C)	-35-45