Lynx-L 36W BL368

SpeciaLITE





These BL368 tubes emit an upgraded highly concentrated radiation with peak around 368nm. Flying insect - eye sensitivity is generally at or near this frequency 100% improvement in effectiveness (at 368nm). Depreciation of UV-A output over time is significantly reduced (80% at 5000hrs of original 100 hour output).

Technical Assets

Dimensions (mm)



Photometrics

General data

Product name	Lynx-L 36W BL368
Technology	Special applications
Lamp shape	U shape
Cap/Base	2G11
Lamp finish	Frosted/Coated
Fixture rating	Enclosed
General application	SPG
Operating temperature range (°C)	-15°C+50°C
ETIM Class	EC002962
E-number Fl	4940710

Optical data

Light colour	BL368 Blacklight
Adjustable chromaticity	Ν
Photobiological Risk Group	RG0
Electrical data	
Power consumption (W)	36
Wattage (W)	36
Primary Supply/Product voltage - min (V)	230
Primary Supply/Product voltage - max (V)	240
Control gear required	Yes
Dimmable	No
Dimming method	N/A



Lynx-L 36W BL368

Item No: 0025710



Lifetime data

Average life (Nominal) (h)	15000
Physical data	
Nominal Product Height (mm)	404
Nominal Product Diameter (mm)	44
Weight (kg)	0.095
Packaging	

5410288257105 **Product EAN number** Packaging single length / height (cm) 42.53 Packaging single width (cm) 4.63 Packaging single depth (cm) 2.37 DUN14 (inner) 15410288257102 Units per outer package 10 Packaging outer length / height (cm) 44.6 Packaging outer width (cm) 14.0 Packaging outer depth (cm) 10.0

Safety data

Lamp mercury content (mg)	3.5
Optimal operating condition (°C)	-15-50
Breakage cleaning instructions	Applicable
Recommendation for disposal at end of life	Applicable
Special purpose lamp	Yes
Special purpose lamp Intended purpose	Yes Flykilling - Insect attraction
	Flykilling - Insect