


## 28PV-16031603-1: Double Backplate elbow female, build in 16x3/8"x16x3/8"



### Commercial information

#### Basic unit dimensions

Height	37 mm
Length	120 mm
Width	69 mm
Net weight	0.329 kg

#### Certificates

ATG, DVGW Wasser, ETA, KIWA, ÖVGW Wasser, WRAS, KOMO, STF, ÖN EN 21003-2/-3, GOST-R, ITC, TSU, QB (CSTBat), AFNOR, ACS, PZH, DNV-GL, Sans 21003, Kontrol Biro, EMI

#### Applications

Potable water, Heating, Cooling, Compressed air, Sanitary

#### Solutions

Building installations, Industry, Utility, Shipbuilding

## Technical characteristics

System specific	✓	Outer pipe diameter connection	16 Millimetre
Housing material	Brass	Distance centre-to-centre	120 Millimetre
Surface protection	Untreated	Max. operating pressure at 20 °C	16 Bar
Connection	Press sleeve	Medium temperature (continuous)	-10 70 Degrees celsius
Contour code	TH		
With connection indicator	✗		
With protective cap	✗		
With soundproofing set	✗		
With thermal insulation	✗		
DVGW quality mark for gas	✗		
DVGW quality mark for water	✓		
Compliant with NF 545	✗		
KOMO certified	✓		