

Specifications



Photo is representative



Eaton RD100-3-SCCR

Eaton Bussmann series RD non-fused rotary disconnect switch, Standard switch, Front handle operation, 600 Vac, 250 Vdc, 100A, Non-fused disconnect switch

General specifications

PRODUCT NAME	Eaton Bussmann series RD non-fused rotary disconnect switch
CATALOG NUMBER	RD100-3-SCCR
UPC	051712402422
PRODUCT LENGTH/DEPTH	11 in
PRODUCT HEIGHT	6.5 in
PRODUCT WIDTH	11 in
PRODUCT WEIGHT	5.32 lb
WARRANTY	Not Applicable
COMPLIANCES	Not Applicable RoHS Compliant
PRODUCT TYPE	Non-fused disconnect switch

Electrical rating

AMPERAGE RATING	100A
VOLTAGE RATING	600 Vac, 250 Vdc

Physical details

OPERATING TEMPERATURE - MAX	70 °C
OPERATING TEMPERATURE - MIN	-20 °C

Resources

CATALOGS	Bussmann series complete full line catalog no. 1007 RD100-3-SCCR~Switch 100A Non-F 3P UL98
MULTIMEDIA	Bussmann series Fuseology
SPECIFICATIONS AND DATASHEETS	Eaton Specification Sheet - RD100-3-SCCR

PROJECT NAME:

PROJECT NUMBER:

PREPARED BY:

DATE:



Eaton Corporation plc Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2026 Eaton. All Rights Reserved.

Follow us on social media to get the latest product and support information.

