

Data Sheet | Item Number: 231-129

Coding key; snap-on type; light gray

<https://www.wago.com/231-129>



Color: ■ light gray

Similar to illustration

Physical data

Pin spacing 5/5.08 mm

Mechanical data

Suitable for male connectors

Material data

Note (material data)	Information on material specifications can be found here
Color	light gray
Material group	I
Insulation material	Polyamide (PA66)
Flammability class per UL94	V0
Fire load	0.004 MJ
Weight	0.2 g

Commercial data

Product Group	3 (Multi Conn. System)
eCl@ss 10.0	27-14-11-92
eCl@ss 9.0	27-14-11-92
ETIM 8.0	EC002848
ETIM 7.0	EC002848
PU (SPU)	200 (100) pcs
Packaging type	Box
Country of origin	DE
GTIN	4017332117371
Customs tariff number	39269097900

Environmental Product Compliance

RoHS Compliance Status	Compliant, No Exemption
------------------------	-------------------------

Approvals / Certificates

General approvals **Approvals for marine applications**



Approval	Standard	Certificate Name
CSA DEKRA Certification B.V.	C22.2	1466354

Approval	Standard	Certificate Name
LR Lloyds Register	IEC 61984	96/20035 (E5)

Downloads

Environmental Product Compliance

Compliance Search
Environmental Product Compliance 231-129

Documentation

Additional Information			
Technical Section	03.04.2019	pdf 2010.85 KB	


CAD/CAE-Data

CAD data
2D/3D Models 231-129

CAE data
ZUKEN Portal 231-129

Installation Notes

Coding



Coding a male header – fitting coding key (s).

Subject to changes. Please also observe the further product documentation!

Current addresses can be found at: www.wago.com