

# Finishing set for fourfold potential-free 24 V push button with text field, sterling coated

**121-40250**



Finishing set for a push button with four potential-free 24 V control buttons used to control various lighting points in one or more rooms. There is a text field in the centre section of the finishing set where you can easily add text or an icon. Colour: sterling coated.



## Technical data

Finishing set for fourfold potential-free 24 V push button with text field, sterling coated.

- Function: the two keys (1 per 2 push buttons) are clicked onto the fourfold, potential-free push button at the bottom and the top and are held in place by the snap hooks on the base of the potential-free push button. The back of the two keys is equipped with two legs that push on the push buttons of the base when the key is pressed
- Number of buttons: 4
- Material finishing: polycarbonate (PC) + acrylic-styrene-acrylate (ASA)
- Type of control: push button
- Colour: sterling coated
- Surface treatment: coated
- Text field: the finishing plate with text field is placed in the centre and consists of two parts. The upper part functions as a transparent lens; the lower part holds the finishing plate and label. Each finishing set is supplied with two labels. Dimensions of the label (41 mm x 12 mm)
- Number of lenses: 0
- Dismantling method: pull the central plate off the mechanism
- Minimum ambient temperature: 5 °C
- Maximum ambient temperature: 40 °C
- Protection degree: IP41 for the combination of a mechanism, central plate and faceplate
- Impact resistance: the combination of a mechanism, a central plate and a faceplate has an impact-resistance of IK06
- Fire safety:
  - all plastic components are self-extinguishing (comply with a filament test of 650°C)
  - all plastic components are halogen-free
- Dimensions of finishing: 45 x 45 mm (HxW)

- Dimensions (HxWxD): 44.5 mm x 44.5 mm x 8.6 mm
- Marking: CE