


## Raiden 12KLM

*Raiden IP66 12KLM 830 Symmetric Wide*  
2824008



### Product features

- Outdoor and indoor floodlight range with in house design, comes complete with 1m flying lead and adjustable bracket, aluminium housing, RAL 9022 - Pearl light grey, clear glass diffuser, IP66, IK08, Class I, 3000K, Non-dimming, 12300lm, 90W, 137lm/W, CRI80, Symmetric Wide beam angle 60°, 100000 hrs L90B50 lifespan, 511x319x76mm (LxWxH) dimensions, 6.1kg weight. Ball-impact-resistance according to DIN57710-13 VDE 0710 13/5.81, DIN 18032-3 only with the separate wire guard accessory fitted.





### PRODUCT OVERVIEW

Product name	Raiden IP66 12KLM 830 Symmetric Wide
Technology	LED
Cap/Base	N/A
Housing	Aluminium
General application	Logistics & Industry
ETIM Class	EC001744
Warranty	5 years
Fixture luminous flux (lm)	12300
Luminaire efficacy (lm/W)	137
Colour temperature (K)	3000
Light colour	Warm White
CRI (Ra)	80
Colour Variation Initial (SDCM)	SDCM3
Beam Angle (°)	60
Photobiological Risk Group	RG1
Total power consumption (W)	90
Electrical protection	Class I
Dimmable	No
Dimming method	N/A
Housing colour	RAL 9022 - Pearl light grey
IP rating	IP66
IK rating	IK08
Product EAN number	5025768240081

### PHOTOMETRY

## Raiden 12KLM

Raiden IP66 12KLM 830 Symmetric Wide  
2824008



## TECHNICAL DRAWINGS

