

Beacon LED XXL

BEACON XXL MB 4K L3 BLK

2093046



Product features

- 2093046 BEACON XXL MB 4K L3 BLK Integrated LED spotlight, black RAL 9005, compact and minimalist design, ideal for double height spaces, retail and display applications, die-cast aluminium body, passive cooling heatsink, beam angle: 50° medium beam, optics: Silicone lens for controlled beam, colour temperature: 4000K neutral white, total system power: 48W, total fixture output: 4179lm, luminaire efficacy: 87lm/W, LOR: 100%, colour rendering: Ra 93 typical, LED Chromacity: 3 step MacAdam ellipse, IR/UV free light source without heat radiation, operating voltage: 220-240V / 50-60Hz, drive current: 1200mA, electronic driver, non-dimmable, switched only, power factor: 0.98 electrical protection: CLASS I, 3-circuit track adaptor, suitable for Concord Lytespan 3 track, ingress protection rating: IP20, suitable for internal environment only, horizontal rotation: 355°, vertical tilt: 90°, lockable positioning using Allen key, dime...




PRODUCT OVERVIEW

Product name	BEACON XXL MB 4K L3 BLK
Technology	LED
Cap/Base	N/A
Housing	Aluminium
Mount	Track mounting
Environment	Internal
General application	Retail
ETIM Class	EC001744
E-number FI	4278817
Warranty	5 years
Fixture luminous flux (lm)	4179
Luminaire efficacy (lm/W)	87.06
LOR (%)	100
Colour temperature (K)	4000
Light colour	Neutral White
CRI (Ra)	93
Colour Consistency (SDCM)	3
Beam Angle (°)	50
Photobiological Risk Group	RG1
Total power consumption (W)	48
Electrical protection	Class I
Control gear type	Electronic ballast
Dimming method	N/A
Housing colour	Black
IP rating	IP20
Product EAN number	5025768930463

PHOTOMETRY

Beacon LED XXL BEACON XXL MB 4K L3 BLK 2093046



Distance [m]	Cone diameter [m]	Beam angle [°]	Illuminance [lx]
0.5	0.46	49.6°	1800
1.0	0.92	49.6°	450
1.5	1.39	49.6°	300
2.0	1.85	49.6°	225
2.5	2.31	49.6°	180
3.0	2.77	49.6°	135

Distance [m] Cone diameter [m]
C0-C180 (Half beam angle 49.6°)

TECHNICAL DRAWINGS

