

AN1420: Straight coupling eurocone 3/4" male to 1/2" male adapter



Commercial information

This brass transition fitting has a half-inch male connector with an O-ring on one side and a 3/4" male connector on the other side

Certificates

ATG, ETA, KIWA, ÖVGW Wasser, WRAS, KOMO, ÖN EN 21003-2/-3, GOST-R, ITC, TSU, PZH, DIN CERTCO, CE, DNV-GL, EMI

Applications

Potable water, Heating, Cooling, Sanitary

Solutions

Building installations, Industry, Utility, Shipbuilding

Technical characteristics

Material connection 1	Brass	Bend radius	0 Millimetre
Material quality connection 1	CuZn40Pb2 (CW617N)	Length	25 Millimetre
Material connection 2	Brass	Wrench width union nut	0 Millimetre
Material quality connection 2	CuZn40Pb2 (CW617N)	Medium temperature (continuous)	-10 60 Degrees celsius
Shape	Straight	Max. operating pressure at 20 °C	10 Bar
Reducing	✘	Standard Dimension Ratio (SDR)	0
Eccentric	✘		
System specific	✓		
Nominal diameter connection 1	1/2 inch (15)		
Connection 1	Compression ring		
Nominal diameter connection 2	3/4 inch (20)		
With buffer stud	✘		
Self-sealing	✘		
Ring stiffness class	Other		
With sealing rings/gaskets	✓		
Capped	✘		
With drain valve	✘		
FM quality mark	✘		
LPCB quality mark	✘		
ULC quality mark	✘		
UL quality mark	✘		
VdS quality mark	✘		
KIWA certified	✓		
Gastec QA mark	✘		

Related products