

Product data sheet

Item No. 96.232.7036.7

Cable assembly RST20I3K1-S 15 H 70GN02

Connection cable, male - free end, length 7m, RST20i3, 3 pole, 250/400V, 16A, cable type H07RN-F, cross section 1,5mm<sup>2</sup>, color of coding: green



Item No.	96.232.7036.7
EAN	4015573923232
Order Unit	5 Piece(s)

Certificates / Approvals



Technical data

General

Rated current	16 A
Rated voltage	400 V
Rated impulse voltage	4 kV
Pollution degree	3
Mechanical coding	Yes
Interlockable	Yes
Color of coding/ contact carrier	Green
Marking of poles	
Color of housing inclusive strain relief	Black

Model

Number of poles	3
Nominal cross section conductor	1.5 mm <sup>2</sup>
Degree of protection (IP)	IP66/IP68
Wire strip length	9 mm
sheath strip length	35 mm
Preparation of conductor ends	Ultrasonically compressed wire ends
Cable type	H07RN-F

Cable colour	Black
Cable diameter	9.8 mm
Version of cable	Male - free end

**Material**

Surface finish	Silver-plated
Halogen free	No
Continuous temperature of cable	60 °C
Insulation components continuous temperature	100 °C

**Dimensions**

Total length	7 m
--------------	-----

**Technical drawing**

Codierung	Stecker
	male

Teile-Nr. part-no.	L	Beispiel (Farbe: grün) Typ exempl (colour: green) type
96.232.XX36.7	XX in dm-Schritten	96.232.1036.7 = 10dm/L= 1000mm RST2013K1-S 15 H 10GN02
U6.232.XX36.7	XX in m-Schritten	U6.232.1236.7 = 12 m/L=12000mm RST2013K1-S 15 HX12GN02

Werkstoff/Material	2005	Tag/Date	Name	Zeichnung Nr./Drawing No.	Index
Farbe: grün color: green	05.06.			96.232.0436.7 01K	a

**wieland**

KONFEKT\_LEITUNG  
ready made cable  
Crimpauführung/crimp design K1 L00V