




Color: ■ gray



Dimensions in mm

Male connector, 769 Series, gray

Our male connector (item number 769-636) simplifies electrical installations.

The pcb connector is designed for THT soldering.

Electrical data			
Ratings per IEC/EN			
Nominal voltage (III/3)	250 V		
Rated impulse withstand voltage (III / 3)	4 kV		
Rated voltage (III/2)	500 V		
Rated impulse withstand voltage (III/2)	4 kV		
Rated current	32 A		
Legend (ratings)	(III / 3) ≙ Overvoltage category III / Pollution degree 3		

Connection Data			
Total number of potentials	6	Connection 1	
Number of levels	1	Pole number	6
Preceding contacts	No		



Physical data	
Pin spacing	5 mm / 0.197 inches
Width	33.6 mm / 1.323 inches
Height from the surface	22.2 mm / 0.874 inches
Depth	18.3 mm / 0.72 inches

Mechanical data	
Variable coding	Yes
Mounting type	PCB
Anti-rotation protection	Yes

Plug-in connection	
Contact type (pluggable connector)	Male connector/plug
Connector (connection type)	for PCB
Mismating protection	No
Mating direction to the PCB	90 °

PCB contact	
PCB contact	THT

Material data	
Note (material data)	Information on material specifications can be found here
Color	gray
Material group	I
Insulation material (main housing)	Polyamide (PA66)
Flammability class per UL94	V0
Fire load	0.133 MJ
Weight	6.2 g

Environmental requirements	
Processing temperature	-35 ... +85 °C
Continuous operating temperature	-60 ... +105 °C

Commercial data	
Product Group	18 (X-COM-System)
PU (SPU)	50 pcs
Packaging type	Box
Country of origin	PL
GTIN	4044918270687
Customs tariff number	85366930000



Product Classification		
UNSPSC		39121409
eCl@ss 10.0		27-44-04-02
eCl@ss 9.0		27-44-04-02
ETIM 9.0		EC002637
ETIM 10.0		EC002637
ECCN		NO US CLASSIFICATION

Environmental Product Compliance		
RoHS Compliance Status		Compliant, No Exemption

Approvals / Certificates

General approvals			Declarations of conformity and manufacturer's declarations		
Approval	Standard	Certificate Name	Approval	Standard	Certificate Name
CCA DEKRA Certification B.V.	EN 60947	NTR NL-7626	EU-Declaration of Confor- mity WAGO GmbH & Co. KG	-	-
CCA DEKRA Certification B.V.	EN 61984	2190419.02	Railway WAGO GmbH & Co. KG	-	Z00004428.000
CCA DEKRA Certification B.V.	IEC 61984	NL-47799/A1			
CSA CSA Group	C22.2	1101144			
KEMA/KEUR DEKRA Certification B.V.	EN 60947	2190419.01			
UL Underwriters Laboratories Inc.	UL 1059	E45172			
UL Underwriters Laboratories Inc.	UL 1977	E 45171			

Approvals for marine applications

Approval	Standard	Certificate Name
DNV GL Det Norske Veritas, Ger- manischer Lloyd	-	TAE00001V2
PRS Polski Rejestr Statków	-	TE/1094/880590/23



Downloads

Environmental Product Compliance

Compliance Search			
Environmental Product Compliance 769-636			

Documentation

Bid Text			
769-636	19.02.2019	xml 2.96 KB	
769-636	04.10.2017	doc 25.00 KB	

CAD/CAE-Data

CAD data	
2D/3D Models 769-636	

CAE data	
ZUKEN Portal 769-636	

PCB Design	
Symbol and Footprint via SamacSys 769-636	
Symbol and Footprint via Ultra Librarian 769-636	

1 Compatible Products

1.1 System counterpart

1.1.1 Female connector/socket



Item No.: [769-106](#)

1-conductor female connector; CAGE CLAMP®; 4 mm²; Pin spacing 5 mm; 6-pole; coding finger; 4,00 mm²; gray

Item No.: [769-106/021-000](#)

1-conductor female connector; CAGE CLAMP®; 4 mm²; Pin spacing 5 mm; 6-pole; coding finger; Lateral locking levers; 4,00 mm²; gray

Item No.: [769-126](#)

2-conductor female connector; CAGE CLAMP®; 4 mm²; Pin spacing 5 mm; 6-pole; coding finger; 4,00 mm²; gray

1.2 Optional Accessories

1.2.1 Coding

1.2.1.1 Coding



Item No.: 769-435

Coding pin; for coding of female plugs; for carrier terminal blocks / male connectors; orange

1.2.2 Marking

1.2.2.1 Marking strip

Item No.: 210-833

Marking strips; 25 m on roll; 6 mm wide;
plain; Self-adhesive; white



Item No.: 210-831

Marking strips; on reel; 2.3 mm wide;
plain; Self-adhesive; white



Item No.: 210-832


Marking strips; on reel; 3 mm wide; plain;
Self-adhesive; white

Item No.: 210-834

Marking strips; on reel; 5 mm wide; plain;
Self-adhesive; white

Installation Notes


Installation




L6 = L4 + 2.6 mm
L4 = pole no. x pin spacing + 1.7 mm

Cutout
Male headers with solder pins


Application




Male headers with straight solder pins and 1-conductor female plugs (picture shows a relay module)



Male headers with solder pins for printed circuit boards



Pluggable PCB connection
Connection to a relay module inside the
switchgear cabinet



Male headers with solder pins
Integrating PCB components into the sys-
tem wiring.