

0041075	DATA SHEET	
valid from: 12.06.2026	ÖLFLEX® CRANE CF	

Application

ÖLFLEX® CRANE CF are weatherproof, screened power flat cables for use under harsh environmental conditions. They are also suitable for use in dry, damp or wet areas. They are suitable for outdoor use if the indicated temperature range is observed. The separate core screening made of copper braiding is a protection against electrical interference.

Application range: In machine tools, conveyor systems, sewage plants, high rack facilities, in crane systems on building sites and shipyards, overhead crane systems and in other plant engineering and constructions, where the cables are exposed turnings only in one level.

Design

Design	based on VDE 0250-809 (NGFLGÖU - unscreened)
Conductor	fine resp. superfine wire strands of bare copper acc. to IEC 60228 resp. EN IEC 60228, Class 6: starting at 1,5 mm ² up to 25 mm ² Class 5: starting at 35 mm ² up to 95 mm ²
Insulation	rubber compound 3GI3 acc. to VDE 0207-20
Core identification code	acc. to VDE 0293-1, with GN/YE ground conductor up to 5 cores coloured in acc. to HD 308 S2 that is VDE 0293-308 starting at 6 cores: Black cores with white numbers acc. to EN 50334
Screen	separately per each single core: plastic foil wrapping tinned copper braiding, coverage 85 % (nominal value) plastic foil wrapping
Outer sheath	rubber compound 5GM3 acc. to VDE 0207-21, Colour: black, similar RAL 9005

Electrical properties at 20 °C

Nominal voltage	U ₀ /U: 300/500 V
Test voltage	c/c 3000 V AC c/s 2000 V AC

Mechanical and thermal properties

Minimum bending radius	occasional flexing: 10 x outer diameter fixed installation: 4 x outer diameter
Temperature range	permitted surface temperature: flexing: -25 °C up to +80 °C fixed installation -40 °C up to +80 °C max. permitted operating temperature: at the conductor: +90 °C
Flammability	flame retardant acc. to IEC 60332-1-2 resp. EN 60332-1-2
Oil resistance	acc. to VDE 0207-21, 5GM3

Tests	acc. to IEC 60811 resp. EN 60811, EN 50395, EN 50396
General requirements	These cables are conform to the EU-Directive 2014/35/EU (Low Voltage Directive)
Environmental information	These cables meet the substance-specific requirements of the EU Directive 2011/65/EU (RoHS).

Creator: MAIH / PDC	Document: DB0041075EN	Page 1 of 1
Released: ALTE / PDC	Version: 05	