



## HNAFL-DN50: Flange connection HNA Ø75 x DN50



### Commercial information

The Super Size range includes the Henco multilayer pipe and Henco fittings with diameters of 75-90, with reducers to diameters of 32-40-50-63. The connectors ensure a complete multilayer pipe system with numerous variations for headers and risers. The many combination possibilities and the revolutionary connection technology make this modular system extremely flexible.

Like all Henco press fittings, the Super Size fittings come with leak detection and are made from high-performance plastic PVDF. These properties make the Henco Super Size fittings suited for different applications, such as drinking water installations, heating installations and installations in the chemical and food industries.

#### Basic unit dimensions

Height	70 mm
Length	165 mm
Width	165 mm
Net weight	3.700 kg

#### Certificates

#### Applications

Potable water, Heating, Cooling, Sanitary

#### Solutions

Building installations, Industry, Utility

## Technical characteristics

Material connection 1	Stainless steel	Bend radius	0 Millimetre
Material quality connection 1	Stainless steel 304 (1.4301)	Length	165 Millimetre
Surface protection connection 1	Untreated	Medium temperature (continuous)	-10 70 Degrees celsius
Surface treatment connection 1	Untreated	Max. operating pressure at 20 °C	10 Bar
Material connection 2	Stainless steel		
Material quality connection 2	Stainless steel 304 (1.4301)		
Shape	Straight		
Reducing	✓		
Eccentric	✗		
System specific	✓		
Nominal diameter connection 2	3/4 inch (20)		
Main colour fitting	Grey		
Self-sealing	✗		
Ring stiffness class	Other		
With sealing rings/gaskets	✗		
Capped	✗		
With drain valve	✗		
With de-aerator	✗		
FM quality mark	✗		
LPCB quality mark	✗		
ULC quality mark	✗		
UL quality mark	✗		
VdS quality mark	✗		
KIWA certified	✗		
Gastec QA mark	✗		