

BAP-FFV1604: Inox ball valve with handle, press x female Ø16 x 1/2"



Commercial information

With the BAP-FFV valve assortment, Henco offers stainless steel valves that guarantee an extra-long life, regardless of water hardness. They are also the right solution for "heavy duty" environments such as hospitals, farms, car washes, laboratories, etc. Also suitable for osmosis and demineralised water.

This stainless steel valve offers the user a unique range of benefits:

- · Connections: press x press
- KIWA and DVGW certified
- Available in diameters from 16 to 32 mm
- With removable levers
- · Equipped with Leak Before Press functionality
- · With color indication for water type

Certificates

KIWA SE, KIWA

Applications

Potable water, Heating, Compressed air, Sanitary

Solutions

Building installations, Industry, Utility



Technical characteristics

Housing material	Stainless steel	Outer pipe diameter connection 2
Material quality	Stainless steel 316 L (1.4404)	Medium temperature (continuous)
Surface protection housing	None	Length of connection 1
Material ball	Stainless steel	Working length connection 1
Surface protection ball	None	Length of connection 2
Material spindle	Stainless steel	Working length connection 2
Material primary spindle seal	Other	Handgrip length
Material secondary spindle seal	Other	
Nominal diameter connection 1	1/2 inch (15)	
Connection 1	Internal thread cylindrical BSPP-G (ISO 228-1)	
With coupling connection 1	×	
Nominal diameter connection 2	DN 8	
Connection 2	Press sleeve	
With coupling connection 2	×	
Contour code connection 2	TH/BE	
Article compression class	PN 16	
With drain valve	×	
With drain possibility (connection)	×	
With filter	×	
With thermometer	×	
Model	Straight	
With insulation shell	×	
FM quality mark	×	
UL quality mark	×	
ULC quality mark	×	
LPCB quality mark	×	
Fire-safe	×	
Medically clean	×	
Grease-free	×	
Operation	Lever handle	
Full bore	✓	
VdS quality mark	×	
DVGW quality mark for gas	×	
DVGW quality mark for water	×	
KIWA certified	✓	
Type approval according to BBR/EKS	×	

Related products

Product codeGTINDescriptionBE1605414764437456Henco Jaws (universal) BE/TH-Profile 16x2

 ${\sf PRESSCHECK1432} \quad 05414764437456 \quad {\sf Henco\ Tool\ to\ control\ the\ accuracy\ of\ a\ pressing\ \varnothing 14-32}$

Image

16 Millimetre

46.2 Millimetre

64.3 Millimetre

33.5 Millimetre

12.2 Millimetre

27 Millimetre

-10|70 Degrees celsius





