

## BAP-FFV2626: Inox ball valve with handle, 2X pressfitting Ø26



### Commercial information

With the BAP-FFV valve assortment, Henco offers stainless steel valves that guarantee an extra-long life, regardless of water hardness. They are also the right solution for "heavy duty" environments such as hospitals, farms, car washes, laboratories, etc. Also suitable for osmosis and demineralised water.

This stainless steel valve offers the user a unique range of benefits:

- Connections: press x press
- KIWA and DVGW certified
- Available in diameters from 16 to 32 mm
- With removable levers
- Equipped with Leak Before Press functionality
- With color indication for water type

#### Certificates

KIWA SE, KIWA

#### Applications

Potable water, Heating, Compressed air, Sanitary


#### Solutions

Building installations, Industry, Utility

## Technical characteristics

Housing material	Stainless steel	Outer pipe diameter connection 1	26 Millimetre
Material quality	Stainless steel 316 L (1.4404)	Outer pipe diameter connection 2	26 Millimetre
Surface protection housing	None	Medium temperature (continuous)	-10 70 Degrees celsius
Material ball	Stainless steel	Length of connection 1	67.8 Millimetre
Surface protection ball	None	Working length connection 1	37 Millimetre
Material spindle	Stainless steel	Length of connection 2	67.8 Millimetre
Material primary spindle seal	Other	Working length connection 2	37 Millimetre
Material secondary spindle seal	Other	Handgrip length	12.2 Millimetre
Nominal diameter connection 1	DN 15		
Connection 1	Press sleeve		
With coupling connection 1	✓		
Contour code connection 1	TH/BE		
Nominal diameter connection 2	DN 15		
Connection 2	Press sleeve		
With coupling connection 2	✗		
Contour code connection 2	TH/BE		
Article compression class	PN 16		
With drain valve	✗		
With drain possibility (connection)	✗		
With filter	✗		
With thermometer	✗		
Model	Straight		
With insulation shell	✗		
FM quality mark	✗		
UL quality mark	✗		
ULC quality mark	✗		
LPCB quality mark	✗		
Fire-safe	✗		
Medically clean	✗		
Grease-free	✗		
Operation	Lever handle		
Full bore	✓		
VdS quality mark	✗		
DVGW quality mark for gas	✗		
DVGW quality mark for water	✗		
KIWA certified	✓		
Type approval according to BBR/EKS	✗		

## Related products

Product code	GTIN	Description	Image
BE26	05414764437364	Henco Jaws (universal) BE/TH-Profile 26x3	
PRESSCHECK1432	05414764437364	Henco Tool to control the accuracy of a pressing Ø14-32	