

Walraven BISOFIX® E32 + Bifix® G2

(D0342)

for insulated pipes



Features & benefits

- for combination with elastomeric foam insulation
- vapourproof glueable with pipe insulation
- insulating pipe support with Bifix® G2 clamp
- Bifix® G2 with M8/M10 connection nut
- does not contain CFC, HCFC, formaldehyde or cadmium
- fire class B2
- PIR density for D <80mm = 80kg/m³
- PIR density for D >80mm = 120kg/m³
- product is part of the Walraven UltraProtect® 1000 system
- suitable for in- and outdoor applications
- stands min. 1,000 hours salt spray test (max. 5% red rust) according to ISO 9227
- temperature range -45 °C - +105 °C

Product Number	Outside Pipe Diameter	Connection Thread	Total Width x Total Height x Total Length	Insulation Thickness	Maximum Allowed Load Faz
Reference letter	D	G	W x H x L	Is	Fa,z
Unit description	mm		mm x mm x mm	mm	N
I323008012	12	M8/M10	118 x 100 x 50	32.3	100
I323008015	15	M8/M10	125 x 107 x 50	32.5	100
I323008018	17.2 - 18	M8/M10	125 x 107 x 50	32.3	100
I323008022	21.3 - 22	M8/M10	134 x 115 x 50	33	100
I323008028	27 - 28	M8/M10	148 x 129 x 50	36	100
I323008035	33.7 - 35	M8/M10	148 x 129 x 50	32.5	100
I323008042	42.4	M8/M10	155 x 137 x 50	32.8	150
I323008048	48.3	M8/M10	155 x 137 x 50	32.3	225
I323008054	54	M8/M10	172 x 154 x 50	35.3	225
I323008060	60.3	M8/M10	172 x 154 x 50	32.3	350
I323008064	64	M8/M10	201 x 183 x 50	44	350
I323008070	70	M8/M10	201 x 183 x 50	41	425
I323008076	76.1	M8/M10	201 x 183 x 50	40.3	575
I323008089	88.9	M8/M10	229 x 208 x 50	43.6	875
I323008102	102	M8/M10	248 x 227 x 50	45.2	100
I323008108	108	M8/M10	248 x 227 x 50	42	1,075
I323008114	114	M8/M10	248 x 227 x 50	40.3	1,250
I323008133	133	M8/M10	275 x 253 x 100	42.7	1,475
I323008140	140	M8/M10	275 x 253 x 100	40.3	1,700